

VACUUM TUBE & PIPE PART NUMBER MATRIX

XX

- XXXXX

X

X

XXXX

- XXXX

PROCESS / ALLOY^{1&2}

CW = 316L WELDED

DW = 304L WELDED

SIZE CODE:

ASTM TUBE O.D.

- 1/4 = .25"
- 3/8 = .375"
- 1/2 = .5"
- 3/4 = .75"
- 1 = 1"
- 1-1/2 = 1.5"
- 2 = 2"
- 2-1/2 = 2.5"
- 3 = 3"
- 4 = 4"
- 6 = 6"
- 8 = 8"
- 10 = 10"

NPS PIPE O.D.

300 = DN 300 (NPS 12 / JIS 300A)

END TYPE CODE:

ASTM TUBE

BLANK = SQUARE

NPS PIPE:

L = SQUARE

WALL CODE

TUBE WALL THICKNESS

- .035** = .035"
- .039** = .039"
- .049** = .049"
- .065** = .065"
- .083** = .083"
- .120** = .120"

PIPE SCHEDULE

10S = SCH. 10

FINISH CODE^{3&4}

MP = O.D.=150-grit MP, I.D.=180-grit MP

VB = O.D.=BA/AP, I.D.=BA/AP

ASTM Tube Example:

CW-1/2X.049-VB

VALEX VACUUM SPEC TUBE, 316L WELDED, 1/2" O.D. X .049" WALL, VB FINISH OPTION, SQUARED ENDS

NPS Pipe Example:

DW-300LX10S-VB

VALEX VACUUM SPEC PIPE, 304L WELDED, NPS 12 (DN 300) X SCH 10, VB FINISH OPTION, SQUARED ENDS

NOTES:

1. PER VALEX SPECIFICATION SP-7201
2. PROCESS CODES ARE NOT AVAILABLE FOR ALL SIZE AND FINISH CODES. PLEASE CONTACT VALEX FOR ITEM NUMBER AVAILABILITY.
3. VB FINISH CODE: BA FOR SIZES < 6" AND AP FOR SIZES ≥ 6".
4. FOR EP GRADE, REFER TO 401 PRODUCT LINE



www.valex.com

TITLE

VACUUM FITTINGS & HOSE ITEM NUMBER SCHEME

SPECIFICATION

SP-7200

SHEET

1/4

REV.

M

VACUUM FITTING PART NUMBER MATRIX

XX
MATERIAL / FINISH

STANDARD FINISH SS¹
VA = 304
VD = 304L
VC = 316L
VQ = 316LN

MECHANICAL POLISHED SS
VE = 304
VH = 304L
VG = 316L

ELECTROPOLISHED SS
VK = 304 EP
VN = 304L EP
VM = 316L EP

- XXX
CONFIGURATION CODE

2 = 90° ELBOW, WITH TANGENT
2T = 90° ELBOW, NO TANGENT
2L = 90° ELBOW, EXTENDED TANGENT
2M = 90° ELBOW, MITERED NO TANGENT
2X = 90° ELBOW, MITERED EXTENDED
2K = 45° ELBOW, WITH TANGENT
2N = 45° ELBOW, NO TANGENT
3Y = Y BRANCH
6HS = NIPPLE, HALF, SHORT
6H = NIPPLE, HALF
6HE = NIPPLE, HALF, EXTENDED
6F = NIPPLE, FULL
6FE = NIPPLE, FULL, EXTENDED
7 = TEE, EQUAL
7L = TEE, EQUAL, EXTENDED
7R = TEE, REDUCING
9 = CROSS, 4-WAY
9R = CROSS, 4-WAY REDUCING
9L = CROSS, 4-WAY, EXTENDED
9F = CROSS, 5-WAY
9E = CROSS, 5-WAY, EXTENDED
9S = CROSS, 6-WAY
9T = CROSS, 6-WAY, EXTENDED
9C = CROSS, 6-WAY CUBE
16 = CAP, WELD
31 = REDUCER, CONCENTRIC / CONICAL
31T = REDUCER, CONCENTRIC W/ TANGENT
31L = REDUCER, STRAIGHT
34 = ADAPTER, CONCENTRIC / CONICAL
34L = ADAPTER, CONCENTRIC LOW PROFILE
34T = ADAPTER, CONCENTRIC W/ TANGENT
34S = ADAPTER, STRAIGHT
34V = ADAPTOR, FACE SEAL MALE
34A = ADAPTOR, FACE SEAL FEMALE
34C = ADAPTOR, COMPRESSION
34M = ADAPTOR, NPT MALE
34F = ADAPTOR, NPT FEMALE
34H = ADAPTOR, HOSE
34G = ADAPTOR, GAUGE TEE
38 = FLANGE, BLANK
38W = FLANGE, BLANK, NECK WELD
38Q = FLANGE, BLANK, NECK WELD W/ WELD PREP
38D = FLANGE, BLANK, DOUBLE SIDED
38B = FLANGE, BORED
38S = FLANGE, BORED, SOCKET WELD
38N = FLANGE, BORED, SHORT NECK WELD
38L = FLANGE, BORED, LONG NECK WELD
38K = FLANGE, BORED, NECK WELD
38V = FLANGE, BORED, NECK WELD W/ WELD PREP
38M = FLANGE, BORED, DOUBLE SIDED
38Z = FLANGE, BORED, ZERO LENGTH REDUCER

- X
TYPE CODE

CONNECTION TYPE
W = WELD (BUTTWELD/SOCKET)
Z = FITTING SIZE (NPT, HOSE, FACE-SEAL, COMPRESSION)

FLANGE TYPE
N = NW / KF
K = ISO-K
F = ISO-F (BOLTED)
C = CF

XX
SIZE CODE

TUBE / PIPE / FITTING

TUBE / FITTING O.D.	PIPE O.D.
02 = 1/8"	67 = 1/8 NPS / NPT
04 = 1/4"	68 = 1/4 NPS / NPT
06 = 3/8"	69 = 3/8 NPS / NPT
08 = 1/2"	70 = 1/2 NPS / NPT
10 = 5/8"	71 = 3/4 NPS / NPT
12 = 3/4"	72 = 1 NPS / NPT
14 = 7/8"	74 = 1-1/2 NPS / NPT
16 = 1"	84 = 12 NPS (12.75")
20 = 1-1/4"	
24 = 1-1/2"	
26 = 1-5/8"	
28 = 1-3/4"	
32 = 2"	
40 = 2-1/2"	
48 = 3"	
64 = 4"	
80 = 5"	
96 = 6"	
53 = 8"	
55 = 10"	
57 = 12"	

NW / KF FLANGE³

1A = NW 10 (1.18", 30mm O.D.)
1B = NW 16 (1.18", 30mm O.D.)
1C = NW 25 (1.58", 40mm O.D.)
1D = NW 40 (2.16", 55mm O.D.)
1E = NW 50 (2.95", 75mm O.D.)
1F = NW 20 (1.58", 40mm O.D.)
1G = NW 32 (2.16", 55mm O.D.)
1H = NW 80 (4.33", 110mm O.D.)
1J = NW 100 (5.12", 130mm O.D.)
1K = NW 160 (7.09", 180mm O.D.)

ISO FLANGE

2A = ISO63 (3.74", 95mm O.D.)
2B = ISO80 (4.33", 110mm O.D.)
2C = ISO100 (5.12", 130mm O.D.)
2D = ISO160 (7.09", 180mm O.D.)
2E = ISO200 (9.45", 240mm O.D.)
2F = ISO250 (11.42", 290mm O.D.)
2G = ISO320 (14.75", 370mm O.D.)
2H = ISO400 (17.72", 450mm O.D.)
2J = ISO500 (21.65", 550mm O.D.)

CF FLANGE

3A = 1.33" (1.33", 33.8mm O.D.)
3B = 2.12" (2.12", 53.8mm O.D.)
3C = 2.75" (2.73", 69.3mm O.D.)
3D = 3.38" (3.36", 85.3mm O.D.)
3E = 4.50" (4.47", 113.5mm O.D.)
3F = 4.62" (4.61", 117.1mm O.D.)
3G = 6.00" (5.97", 151.6mm O.D.)
3H = 6.75" (6.73", 170.9mm O.D.)
3J = 8.00" (7.97", 202.4mm O.D.)
3K = 10.00" (9.97", 253.2mm O.D.)
3L = 12.00" (11.97", 304.0mm O.D.)
3M = 13.25" (13.25", 336.6mm O.D.)
3N = 14.00" (14.00", 355.6mm O.D.)
3P = 14.50" (14.50", 368.3mm O.D.)
3Q = 16.50" (16.50", 419.1mm O.D.)

NW / KF FLANGE (CHAIN CLAMP)⁴

5H = NW 80 (4.33", 110mm O.D.)
5J = NW 100 (5.12", 130mm O.D.)
5K = NW 160 (7.09", 180mm O.D.)

x X XX
TYPE SIZE

USED FOR 2ND SIZE: FLANGE, BUTTWELD/SOCKET WELD, OR FITTING

If required, build second size by using two previous columns (type & size code)

EX: VA-7-W12XW08
VA-34M-K2AXZ68
VA-38B-N1BXW06

- XX
ATTRIBUTE CODE

OTHER
BLANK = Configurations not listed below
(Note: for BLANK code, do not include -XX in part number)

ONLY USE FOR CF & ISO-F FLANGES

FF = NON-ROTATABLE
FS = NON-ROTATABLE, TAPPED, INCH
FM = NON-ROTATABLE, TAPPED, METRIC
FR = ROTATABLE
FT = ROTATABLE, TAPPED, INCH
FN = ROTATABLE, TAPPED, METRIC

ONLY USE FOR: CF FLANGED TEES, CF CROSSES, CF REDUCERS, CF HALF & CF FULL NIPPLES


TA = NON-ROTATABLE, ROTATABLE
TB = NON-ROTATABLE, 2 ROTATABLE
TC = 2 NON-ROTATABLE, 2 ROTATABLE
TD = 2 NON-ROTATABLE, 3 ROTATABLE
TE = 3 NON-ROTATABLE, 3 ROTATABLE
TF = NON-ROTATABLE
TG = ROTATABLE

NOTES:

- STANDARD FINISH IS TUMBLE FOR BUTTWELD FITTINGS.
- STANDARD FINISH IS MACHINED FOR FLANGES.
- FLANGE SIZES 1H, 1J, & 1K USE WITH BAND CLAMP
- FLANGE SIZES 5H, 5J, & 5K USE WITH CHAIN CLAMP
- NOT ALL POSSIBLE PART NUMBER CONFIGURATION ARE AVAILABLE. PLEASE CONTACT VALEX FOR AVAILABILITY.

Part Number Examples:

Elbow: VA-2-N1D
Concentric Reducer: VA-31-N1DXN1B
Full Nipple: VA-6F-N1E
Straight Reducer: VA-31L-K2BXK2A
Equal Tee: VA-7-K2AXK2A
Reducing Tee: VA-7R-K2CXK2A
4-Way Reducing Cross: VA-9R-C3DXC3A-TC
Adaptor, FACE-SEAL MALE: VA-34V-C3AXZ04-FF
Adaptor Concentric Reducer.: VA-34-K2AXN1D
Blank Flange: VA-38-N1A
Bored Flange Rotatable: VA-38B-C3HXW80-FR
Zero Length Reducer: VA-38Z-C3GXC3A-FF


 www.valex.com		
TITLE VACUUM FITTINGS & HOSE ITEM NUMBER SCHEME		
SPECIFICATION SP-7200	SHEET 2 OF 4	REV M

VACUUM ACCESSORIES PART NUMBER MATRIX

XX MATERIAL / FINISH	- XXX CONFIGURATION CODE	- X TYPE CODE	XX SIZE CODE	x XX SIZE	- XX (XX) ATTRIBUTE CODE
OTHER MATERIALS V0 = USE FOR: CLAMPS, CAPS, RINGS, GASKETS, O-RINGS, & HARDWARE	13 = CLAMP, SINGLE CLAW 13D = CLAMP, DOUBLE CLAW 13W = CLAMP, WING NUT 13L = CLAMP, LEVER / QUICK 13C = CLAMP, CHAIN 13B = CLAMP, BULKHEAD 16D = CAP, PLASTIC DUST ----- 39 = RING, CENTERING 39C = RING, CENTERING W/ O-RING ASSEMBLY 39M = RING, CENTERING, SCREEN W/ O-RING ASSEMBLY 39N = RING, CENTERING, SCREEN W/ O-RING & SPACER RING ASSEMBLY 39S = RING, SPACER 39D = RING, CENTERING W/ O-RING & SPACER RING ASSEMBLY 39R = RING, ROTATABLE FLANGE RETAINING 39T = RING, OVERPRESSURE 39E = RING, CENTERING W/ O-RING & OVERPRESSURE RING ASSEMBLY 39P = RING, CAPTURE 39F = RING, CENTERING W/ O-RING & CAPTURE RING ASSEMBLY 39L = RING, REDUCING CENTERING W/ O-RING ASSEMBLY ----- 70 = HARDWARE, BOLTS & WASHERS 70B = HARDWARE, BOLTS, NUTS & WASHERS 70C = HARDWARE, 12-PT BOLTS & WASHERS 70D = HARDWARE, 12-PT BOLTS, NUTS & WASHERS 70P = HARDWARE, PLATE NUTS 70Q = HARDWARE, PLATE NUTS & BOLTS 70R = HARDWARE, PLATE NUTS, BOLTS & WASHERS 70S = HARDWARE, PLATE NUTS & 12-PT BOLTS 70T = HARDWARE, PLATE NUTS, 12-PT BOLTS & WASHERS ----- 72R = O-RING 72G = GASKET	FLANGE TYPE¹ N = NW / KF K = ISO-K F = ISO-F (BOLTED) C = CF CENTERING RING TYPE² N = NW / KF S = ISO-K/ISO-F	NW / KF³ 1A = NW10 (1.18", 30mm O.D.) 1B = NW16 (1.18", 30mm O.D.) 1C = NW25 (1.58", 40mm O.D.) 1D = NW40 (2.16", 55mm O.D.) 1E = NW50 (2.95", 75mm O.D.) 1F = NW20 (1.58", 40mm O.D.) 1G = NW32 (2.16", 55mm O.D.) ISO-K / ISO-F 2A = ISO63 (3.74", 95mm O.D.) 2B = ISO80 (4.33", 110mm O.D.) 2C = ISO100 (5.12", 130mm O.D.) 2D = ISO160 (7.09", 180mm O.D.) 2E = ISO200 (9.45", 240mm O.D.) 2F = ISO250 (11.42", 290mm O.D.) 2G = ISO320 (14.75", 370mm O.D.) 2H = ISO400 (17.72", 450mm O.D.) 2J = ISO500 (21.65", 550mm O.D.) CF 3A = 1.33" (1.33", 33.8mm O.D.) 3B = 2.12" (2.12", 53.8mm O.D.) 3C = 2.75" (2.73", 69.3mm O.D.) 3D = 3.38" (3.36", 85.3mm O.D.) 3E = 4.50" (4.47", 113.5mm O.D.) 3F = 4.62" (4.61", 117.1mm O.D.) 3G = 6.00" (5.97", 151.6mm O.D.) 3H = 6.75" (6.73", 170.9mm O.D.) 3J = 8.00" (7.97", 202.4mm O.D.) 3K = 10.00" (9.97", 253.2mm O.D.) 3L = 12.00" (11.97", 304.0mm O.D.) 3M = 13.25" (13.25", 336.6mm O.D.) 3N = 14.00" (14.00", 355.6mm O.D.) 3P = 14.50" (14.50", 368.3mm O.D.) 3Q = 16.50" (16.50", 419.1mm O.D.) ISO-K CLAW CLAMP 4A = ISO63 - ISO100 4B = ISO160 - ISO250 4C = ISO320 - ISO500 4D = ISO63 - ISO250	USED FOR REDUCING CENTERING RING If required, build 2nd size by using previous column (size code) EX: V0-39L-N1FX1C-4CX	CLAMP THREAD / MATERIAL⁴ CA = INCH, ALUMINUM CB = METRIC, ALUMINUM CC = INCH, 316 SS, ZINC PLATED NUT CD = METRIC, 316 SS, ZINC PLATED NUT CE = INCH, 304 SS GASKET MATERIAL G1 = OFHC COPPER G2 = SILVER PLATED OFHC COPPER G3 = PTFE
					FOR THE FOLLOWING CONFIGURATIONS SELECT ONE FROM EACH OPTION:
					RINGS & O-RING MATERIAL
		OPTION 1 - CENTERING RINGS X = NO CENTERING RING 1 = CENTERING RING, ALUMINUM 2 = CENTERING RING, 304 SS 3 = CENTERING RING, 316L SS 4 = CENTERING RING, 316L SS, EP 5 = CENTERING RING, 316 SS 6 = CENTERING RING, 316 SS, EP	OPTION 2 - O-RINGS X = NO O-RING A = NBR (BUNA) B = EPDM C = FKM (VITON) D = SILICONE E = KALREZ 6375 F = KALREZ 8900 G = KALREZ 9100 H = KALREZ 9500 J = KALREZ 8575 K = KALREZ 4079	OPTION 3 - RINGS (OUTER) X = NO RING A = SPACER, ALUMINUM D = OVERPRESSURE, ALUMINUM E = OVERPRESSURE, 304 SS F = OVERPRESSURE, 316 SS G = CAPTURE, ALUMINUM H = CAPTURE, 304 SS J = CAPTURE, 316 SS K = RETAINING, 304 SS	OPTION 4 - O-RING COLOR BLANK = BLACK B = BROWN G = GREEN
					HARDWARE MATERIAL / THREAD
		OPTION 1 - PLATE NUT X = NO PLATE NUT P = PLATE NUT, 304 SS	OPTION 2 - MAT'L and/or THREAD X = NO BOLTS AND WASHERS S = INCH (PLATE NUT) M = METRIC (PLATE NUT) T = INCH, 10-8SS (BOLTS) U = INCH, 10-8SS, SILVER-PLATED (BOLTS) V = METRIC, 10-8SS (BOLTS) W = METRIC, 10-8SS, SILVER-PLATED (BOLTS)	OPTION 3 - BOLT LENGTH (SEE CATALOG FOR LENGTHS) X = NO BOLT A = STANDARD LENGTH A B = STANDARD LENGTH B C = STANDARD LENGTH C	

Part Number Examples:
 Double Claw Clamp: V0-13D-K2B-CA
 Plastic Dust Cap: V0-16D-K2D-PA
 Centering Ring w/ Viton O-ring: V0-39C-K2E-2CX
 Centering Ring w/ Viton O-ring & Aluminum Capture Ring Assembly: V0-39F-N1D-2CG
 Centering Ring: V0-39-K2F4-1XX
 Spacer Ring: V0-39S-K2C-XXA
 Rotatable Flange Retaining Ring: V0-39R-F2A-XXJ
 Reducing Centering Ring w/ O-ring: V0-39L-N1AXN1B-4CX
 Hardware, Plate Nuts: V0-70P-C3B-PSX
 Hardware, Bolts, Nuts & Washers: V0-70B-C3F-XTA
 Hardware, Plate Nuts, Bolts & Washers: V0-70R-C3H-PTA
 Copper Gasket V0-72G-N1C-G1
 Viton O-Ring: V0-72O-K2C-XXC

- NOTES:**
- NW/KF USE ISO FLANGE TYPE FOR FLANGE SIZE ISO 80 & ABOVE.
 - NW/KF CENTERING RINGS ISO 80 & ABOVE USE THE "S" TYPE CODE DESIGNATOR IN P/N.
 - NW/KF USE ISO CENTERING RING SIZE CODES FOR FLANGE SIZE ISO 80 & ABOVE.
 - CHOOSE THE FOLLOWING MATERIAL FOR ISO CLAW CLAMP SIZES:
 4A, 4B & 4C: ALUMINUM, 4C & 4D: STAINLESS STEEL
 - NOT ALL POSSIBLE PART NUMBER CONFIGURATION ARE AVAILABLE.
 PLEASE CONTACT VALEX FOR AVAILABILITY.



www.valex.com

TITLE VACUUM FITTINGS & HOSE ITEM NUMBER SCHEME		
SPECIFICATION SP-7200	SHEET 3 OF 4	REV M

VACUUM BELLOWS & FLEXIBLE HOSE PART NUMBER MATRIX

XX MATERIAL / FINISH ¹	- XXX CONFIGURATION CODE ²	- X TYPE CODE	XX SIZE CODE	X	X TYPE CODE	XX SIZE CODE	- XXX ATTRIBUTE CODE																																											
<p>STANDARD FINISH SS</p> <p>VA = 304 VD = 304L VC = 316L VQ = 316LN VT = V22[®] ALLOY (UNS N06022)* VW = ALLOY 276 (UNS N10276)</p> <p>MECHANICAL POLISHED SS</p> <p>VE = 304 VH = 304L VG = 316L VU = V22[®] ALLOY (UNS N06022)* VY = ALLOY 276 (UNS N10276)</p> <p>ELECTROPOLISHED SS</p> <p>VK = 304 EP VN = 304L EP VM = 316L EP VV = V22[®] ALLOY (UNS N06022)* VZ = ALLOY 276 (UNS N10276)</p>	<p>42B = BELLOWS, FORMED, 316L³ 42E = BELLOWS, EDGE WELDED 42H = HOSE, FORMED 42R = HOSE, BRAIDED FLEXIBLE 42T = BELLOWS, FORMED, 321³</p>	<p>CONNECTION TYPE</p> <p>W = WELD (BUTTWELD/SOCKET) T = COMPRESSION FITTING V = FACE SEAL, MALE U = FACE SEAL, FEMALE</p> <p>FLANGE TYPE</p> <p>N = NW / KF K = ISO-K F = ISO-F (BOLTED) C = CF</p>	<p>TUBE / PIPE / FITTING</p> <table border="0"> <tr> <th style="text-align: left;">TUBE O.D.</th> <th style="text-align: left;">PIPE O.D.</th> </tr> <tr> <td>02 = 1/8"</td> <td>67 = 1/8 NPS / NPT</td> </tr> <tr> <td>04 = 1/4"</td> <td>68 = 1/4 NPS / NPT</td> </tr> <tr> <td>06 = 3/8"</td> <td>69 = 3/8 NPS / NPT</td> </tr> <tr> <td>08 = 1/2"</td> <td>70 = 1/2 NPS / NPT</td> </tr> <tr> <td>10 = 5/8"</td> <td>71 = 3/4 NPS / NPT</td> </tr> <tr> <td>12 = 3/4"</td> <td>72 = 1 NPS / NPT</td> </tr> <tr> <td>14 = 7/8"</td> <td>74 = 1-1/2 NPS / NPT</td> </tr> <tr> <td>16 = 1"</td> <td>84 = 12 NPS (12.75" O.D.)</td> </tr> <tr> <td>20 = 1-1/4"</td> <td></td> </tr> <tr> <td>24 = 1-1/2"</td> <td></td> </tr> <tr> <td>26 = 1-5/8"</td> <td></td> </tr> <tr> <td>28 = 1-3/4"</td> <td></td> </tr> <tr> <td>32 = 2"</td> <td></td> </tr> <tr> <td>40 = 2-1/2"</td> <td></td> </tr> <tr> <td>48 = 3"</td> <td></td> </tr> <tr> <td>64 = 4"</td> <td></td> </tr> <tr> <td>80 = 5"</td> <td></td> </tr> <tr> <td>96 = 6"</td> <td></td> </tr> <tr> <td>53 = 8"</td> <td></td> </tr> <tr> <td>55 = 10"</td> <td></td> </tr> <tr> <td>57 = 12"</td> <td></td> </tr> </table> <p>NW / KF FLANGE</p> <p>1A = NW10 (1.18", 30mm O.D.) 1B = NW16 (1.18", 30mm O.D.) 1C = NW25 (1.58", 40mm O.D.) 1D = NW40 (2.16", 55mm O.D.) 1E = NW50 (2.95", 75mm O.D.) 1F = NW20 (1.58", 40mm O.D.) 1G = NW32 (2.16", 55mm O.D.) 1H = NW80 (4.33", 110mm O.D.) 1J = NW100 (5.12", 130mm O.D.) 1K = NW160 (7.09", 180mm O.D.)</p> <p>ISO-K / ISO-F FLANGE</p> <p>2A = ISO63 (3.74", 95mm O.D.) 2B = ISO80 (4.33", 110mm O.D.) 2C = ISO100 (5.12", 130mm O.D.) 2D = ISO160 (7.09", 180mm O.D.) 2E = ISO200 (9.45", 240mm O.D.) 2F = ISO250 (11.42", 290mm O.D.) 2G = ISO320 (14.75", 370mm O.D.) 2H = ISO400 (17.72", 450mm O.D.) 2J = ISO500 (21.65", 50mm O.D.)</p> <p>CF FLANGE</p> <p>3A = 1.33" (1.33", 33.8mm O.D.) 3B = 2.12" (2.12", 53.8mm O.D.) 3C = 2.75" (2.73", 69.3mm O.D.) 3D = 3.38" (3.36", 85.3mm O.D.) 3E = 4.50" (4.47", 113.5mm O.D.) 3F = 4.62" (4.61", 117.1mm O.D.) 3G = 6.00" (5.97", 151.6mm O.D.) 3H = 6.75" (6.73", 170.9mm O.D.) 3J = 8.00" (7.97", 202.4mm O.D.) 3K = 10.00" (9.97", 253.2mm O.D.) 3L = 12.00" (11.97", 304.0mm O.D.) 3M = 13.25" (13.25", 336.6mm O.D.) 3N = 14.00" (14.00", 355.6mm O.D.) 3P = 14.50" (14.50", 368.3mm O.D.) 3Q = 16.50" (16.50", 419.1mm O.D.)</p>	TUBE O.D.	PIPE O.D.	02 = 1/8"	67 = 1/8 NPS / NPT	04 = 1/4"	68 = 1/4 NPS / NPT	06 = 3/8"	69 = 3/8 NPS / NPT	08 = 1/2"	70 = 1/2 NPS / NPT	10 = 5/8"	71 = 3/4 NPS / NPT	12 = 3/4"	72 = 1 NPS / NPT	14 = 7/8"	74 = 1-1/2 NPS / NPT	16 = 1"	84 = 12 NPS (12.75" O.D.)	20 = 1-1/4"		24 = 1-1/2"		26 = 1-5/8"		28 = 1-3/4"		32 = 2"		40 = 2-1/2"		48 = 3"		64 = 4"		80 = 5"		96 = 6"		53 = 8"		55 = 10"		57 = 12"		SEE PREVIOUS COLUMN "TYPE CODE" FOR OPTIONS	SEE PREVIOUS COLUMN "SIZE CODE" FOR OPTIONS	<p>BELLOWS LENGTH</p> <p>2.5 = 2.5" 3.0 = 3.0" 3.2 = 3.2" 3.5 = 3.5" 4.0 = 4.0" 4.2 = 4.2" 5.0 = 5.0" 5.2 = 5.2" 6.0 = 6.0" 7.0 = 7.0" 8.0 = 8.0" 8.2 = 8.2" 9.0 = 9.0"</p> <p>HOSE LENGTH</p> <p>10 = 10.0" 12 = 12.0" 18 = 18.0" 24 = 24.0" 30 = 30.0" 36 = 36.0" 42 = 42.0" 48 = 48.0" 54 = 54.0" 60 = 60.0" 72 = 72.0" 84 = 84.0" 96 = 96.0" 108 = 108.0" 120 = 120.0" 984 = 984.0"</p>
TUBE O.D.	PIPE O.D.																																																	
02 = 1/8"	67 = 1/8 NPS / NPT																																																	
04 = 1/4"	68 = 1/4 NPS / NPT																																																	
06 = 3/8"	69 = 3/8 NPS / NPT																																																	
08 = 1/2"	70 = 1/2 NPS / NPT																																																	
10 = 5/8"	71 = 3/4 NPS / NPT																																																	
12 = 3/4"	72 = 1 NPS / NPT																																																	
14 = 7/8"	74 = 1-1/2 NPS / NPT																																																	
16 = 1"	84 = 12 NPS (12.75" O.D.)																																																	
20 = 1-1/4"																																																		
24 = 1-1/2"																																																		
26 = 1-5/8"																																																		
28 = 1-3/4"																																																		
32 = 2"																																																		
40 = 2-1/2"																																																		
48 = 3"																																																		
64 = 4"																																																		
80 = 5"																																																		
96 = 6"																																																		
53 = 8"																																																		
55 = 10"																																																		
57 = 12"																																																		

NOTES:

- FINISH OPTIONS ARE FOR END CONNECTIONS ONLY.
- ALL BRAIDED HOSES ARE 304/304L.
- BELLOWS BODY MATERIAL ONLY.
- NOT ALL POSSIBLE PART NUMBER CONFIGURATION ARE AVAILABLE. PLEASE CONTACT VALEX FOR AVAILABILITY.

*MATERIAL: HAYNES HASTELLOY[®] C-22[®] IS AVAILABLE UPON REQUEST. HASTELLOY AND C-22 ARE REGISTERED TRADEMARKS OF HAYNES INTERNATIONAL INC.

Part Number Examples:

Bellows, 12" Length: VM-42B-N1CXN1C-4.0
Bellows, 12" Length: VM-42B-K2BXK2A-4.0
Hose, 12" Length: VM-42H-U04XU04-12
Hose, 120" Length: VM-42H-T04XT04-120

 www.valex.com		
TITLE VACUUM FITTINGS & HOSE ITEM NUMBER SCHEME		
SPECIFICATION SP-7200	SHEET 4 OF 4	REV M