



# Reducing Tee

JIS B2312 / B2313 Standard, JIS Pipe

Product Lines					Dimensions in Millimeters									
401	LDEP	201	101	CFOS	Size	O.D. 1	5S Wall 1	10S Wall 1	O.D. 2	5S Wall 2	10S Wall 2	A	B	
•		•	•	•	20A x 15A	27.2	1.65	2.10	21.7	1.65	2.10	28.6	28.6	
•		•	•	•	25A x 15A	34.0	1.65	2.80	21.7	1.65	2.10	38.1	38.1	
•		•	•	•	25A x 20A	34.0	1.65	2.80	27.2	1.65	2.10	38.1	38.1	
•		•	•	•	32A x 15A	42.7	1.65	2.80	21.7	1.65	2.10	47.6	47.6	
•		•	•	•	32A x 20A	42.7	1.65	2.80	27.2	1.65	2.10	47.6	47.6	
•	•	•	•	•	32A x 25A	42.7	1.65	2.80	34.0	1.65	2.80	47.6	47.6	
•		•	•	•	40A x 15A	48.6	1.65	2.80	21.7	1.65	2.10	57.2	57.2	
•		•	•	•	40A x 20A	48.6	1.65	2.80	27.2	1.65	2.10	57.2	57.2	
•	•	•	•	•	40A x 25A	48.6	1.65	2.80	34.0	1.65	2.80	57.2	57.2	
•	•	•	•	•	40A x 32A	48.6	1.65	2.80	42.7	1.65	2.80	57.2	57.2	
•		•	•	•	50A x 20A	60.5	1.65	2.80	27.2	1.65	2.10	63.5	44.5	
•	•	•	•	•	50A x 25A	60.5	1.65	2.80	34.0	1.65	2.80	63.5	50.8	
•	•	•	•	•	50A x 32A	60.5	1.65	2.80	42.7	1.65	2.80	63.5	57.2	
•	•	•	•	•	50A x 40A	60.5	1.65	2.80	48.6	1.65	2.80	63.5	60.3	
•	•	•	•	•	65A x 25A	76.3	2.10	3.00	34.0	1.65	2.80	76.2	57.2	
•	•	•	•	•	65A x 32A	76.3	2.10	3.00	42.7	1.65	2.80	76.2	63.5	
•	•	•	•	•	65A x 40A	76.3	2.10	3.00	48.6	1.65	2.80	76.2	66.7	
•	•	•	•	•	65A x 50A	76.3	2.10	3.00	60.5	1.65	2.80	76.2	69.9	
•	•	•	•	•	80A x 32A	89.1	2.10	3.00	42.7	1.65	2.80	85.7	69.9	
•	•	•	•	•	80A x 40A	89.1	2.10	3.00	48.6	1.65	2.80	85.7	73.0	
•	•	•	•	•	80A x 50A	89.1	2.10	3.00	60.5	1.65	2.80	85.7	76.2	
•	•	•	•	•	80A x 65A	89.1	2.10	3.00	76.3	2.10	3.00	85.7	82.6	
•	•	•	•	•	90A x 40A	101.6	2.10	3.00	48.6	1.65	2.80	95.3	79.4	
•	•	•	•	•	90A x 50A	101.6	2.10	3.00	60.5	1.65	2.80	95.3	82.6	
•	•	•	•	•	90A x 65A	101.6	2.10	3.00	76.3	2.10	3.00	95.3	88.9	
•	•	•	•	•	90A x 80A	101.6	2.10	3.00	89.1	2.10	3.00	95.3	92.1	
•	•	•	•	•	100A x 40A	114.3	2.10	3.00	48.6	1.65	2.80	104.8	85.7	
•	•	•	•	•	100A x 50A	114.3	2.10	3.00	60.5	1.65	2.80	104.8	88.9	
•	•	•	•	•	100A x 65A	114.3	2.10	3.00	76.3	2.10	3.00	104.8	95.3	
•	•	•	•	•	100A x 80A	114.3	2.10	3.00	89.1	2.10	3.00	104.8	98.4	
•	•	•	•	•	100A x 90A	114.3	2.10	3.00	101.6	2.10	3.00	104.8	101.6	
•	•	•	•	•	125A x 50A	139.8	2.80	3.40	60.5	1.65	2.80	123.8	104.8	
•	•	•	•	•	125A x 65A	139.8	2.80	3.40	76.3	2.10	3.00	123.8	108.0	
•	•	•	•	•	125A x 80A	139.8	2.80	3.40	89.1	2.10	3.00	123.8	111.1	
•	•	•	•	•	125A x 90A	139.8	2.80	3.40	101.6	2.10	3.00	123.8	114.3	
•	•	•	•	•	125A x 100A	139.8	2.80	3.40	114.3	2.10	3.00	123.8	117.5	
•	•	•	•	•	150A x 65A	165.2	2.80	3.40	76.3	2.10	3.00	142.9	120.7	
•	•	•	•	•	150A x 80A	165.2	2.80	3.40	89.1	2.10	3.00	142.9	123.8	
•	•	•	•	•	150A x 90A	165.2	2.80	3.40	101.6	2.10	3.00	142.9	127.0	
•	•	•	•	•	150A x 100A	165.2	2.80	3.40	114.3	2.10	3.00	142.9	130.2	
•	•	•	•	•	150A x 125A	165.2	2.80	3.40	139.8	2.80	3.40	142.9	136.5	
•	•	•	•	•	200A x 90A	216.3	2.80	4.00	101.6	2.10	3.00	177.8	152.4	
•	•	•	•	•	200A x 100A	216.3	2.80	4.00	114.3	2.10	3.00	177.8	155.6	
•	•	•	•	•	200A x 125A	216.3	2.80	4.00	139.8	2.80	3.40	177.8	161.9	
•	•	•	•	•	200A x 150A	216.3	2.80	4.00	165.2	2.80	3.40	177.8	168.3	
•	•	•	•	•	250A x 100A	267.4	3.40	4.00	114.3	2.10	3.00	215.9	184.2	
•	•	•	•	•	250A x 125A	267.4	3.40	4.00	139.8	2.80	3.40	215.9	190.5	
•	•	•	•	•	250A x 150A	267.4	3.40	4.00	165.2	2.80	3.40	215.9	193.7	
•	•	•	•	•	250A x 200A	267.4	3.40	4.00	216.3	2.80	4.00	215.9	203.2	
•	•	•	•	•	300A x 125A	318.5	4.00	4.50	139.8	2.80	3.40	254.0	215.9	
•	•	•	•	•	300A x 150A	318.5	4.00	4.50	165.2	2.80	3.40	254.0	219.1	
•	•	•	•	•	300A x 200A	318.5	4.00	4.50	216.3	2.80	4.00	254.0	228.6	
•	•	•	•	•	300A x 250A	318.5	4.00	4.50	267.4	3.40	4.00	254.0	241.3	
•	•	•	•	•	350A x 150A	355.6	4.00	5.00	165.2	2.80	3.40	279.4	238.1	
•	•	•	•	•	350A x 200A	355.6	4.00	5.00	216.3	2.80	4.00	279.4	247.7	
•	•	•	•	•	350A x 250A	355.6	4.00	5.00	267.4	3.40	4.00	279.4	257.2	
•	•	•	•	•	350A x 300A	355.6	4.00	5.00	318.5	4.00	4.50	279.4	269.9	
•	•	•	•	•	400A x 150A	406.4	4.50	5.00	165.2	2.80	3.40	304.8	263.5	
•	•	•	•	•	400A x 200A	406.4	4.50	5.00	216.3	2.80	4.00	304.8	273.1	

• • • •	400A x 250A	406.4	4.50	5.00	267.4	3.40	4.00	304.8	282.6
• • • •	400A x 300A	406.4	4.50	5.00	318.5	4.00	4.50	304.8	295.3
• • • •	400A x 350A	406.4	4.50	5.00	355.6	4.00	5.00	304.8	304.8
• • • •	450A x 200A	457.2	4.50	5.00	216.3	2.80	4.00	342.9	298.5
• • • •	450A x 250A	457.2	4.50	5.00	267.4	3.40	4.00	342.9	308.0
• • • •	450A x 300A	457.2	4.50	5.00	318.5	4.00	4.50	342.9	320.7
• • • •	450A x 350A	457.2	4.50	5.00	355.6	4.00	5.00	342.9	330.2
• • • •	450A x 400A	457.2	4.50	5.00	406.4	4.50	5.00	342.9	330.2
• • • •	500A x 200A	508.0	5.00	5.50	216.3	2.80	4.00	381.0	323.9
• • • •	500A x 250A	508.0	5.00	5.50	267.4	3.40	4.00	381.0	333.4
• • • •	500A x 300A	508.0	5.00	5.50	318.5	4.00	4.50	381.0	346.1
• • • •	500A x 350A	508.0	5.00	5.50	355.6	4.00	5.00	381.0	355.6
• • • •	500A x 400A	508.0	5.00	5.50	406.4	4.50	5.00	381.0	355.6
• • • •	500A x 450A	508.0	5.00	5.50	457.2	4.50	5.00	381.0	368.3
• • • •	550A x 400A	558.0	5.00	5.50	406.4	4.50	5.00	419.1	381.0
• • • •	550A x 450A	558.0	5.00	5.50	457.2	4.50	5.00	419.1	393.7
• • • •	550A x 500A	558.0	5.00	5.50	508.0	5.00	5.50	419.1	406.4
• • • •	600A x 450A	609.6	5.50	6.50	457.2	4.50	5.00	431.8	419.1
• • • •	600A x 500A	609.6	5.50	6.50	508.0	5.00	5.50	431.8	431.8
• • • •	600A x 550A	609.6	5.50	6.50	558.8	5.00	5.50	431.8	431.8
• • • •	650A x 500A	660.4	5.50	8.00	508.0	5.00	5.50	495.3	457.2
• • • •	650A x 550A	660.4	5.50	8.00	558.8	5.00	5.50	495.3	469.9
• • • •	650A x 600A	660.4	5.50	8.00	609.6	5.50	6.50	495.3	482.6
• • • •	700A x 550A	711.2	5.50	8.00	558.8	5.00	5.50	520.7	495.3
• • • •	700A x 600A	711.2	5.50	8.00	609.6	5.50	6.50	520.7	508.0
• • • •	700A x 650A	711.2	5.50	8.00	660.4	5.50	8.00	520.7	520.7
• • • •	750A x 600A	762.0	6.50	8.00	609.6	5.50	6.50	558.8	533.4
• • • •	750A x 650A	762.0	6.50	8.00	660.4	5.50	8.00	558.8	546.1
• • • •	750A x 700A	762.0	6.50	8.00	711.2	5.50	8.00	558.8	546.1
• • • •	800A x 650A	812.8	N/A	8.00	660.4	5.50	8.00	596.9	571.5
• • • •	800A x 700A	812.8	N/A	8.00	711.2	5.50	8.00	596.9	571.5
• • • •	800A x 750A	812.8	N/A	8.00	762.0	6.50	8.00	596.9	584.2

