

CONFIGURATION

38WN

Weld Neck Flange

JIS B2220 Standard, Nominal Pressure 5K

Product Lines					Dimensions in Millimeters										
401	LDEP	201	101	CFOS	Size	A	B	C	D	E	F	G	H	I	# of Bolts
•					10A	75	55	39	12.7	17.3	12	1	9	24	4
•		•	•		15A	80	60	44	16.1	21.7	12	1	9	25	4
•		•	•		20A	85	65	49	21.6	27.2	12	1	10	28	4
•	•	•	•	•	25A	95	75	59	27.6	34.0	12	1	10	30	4
•	•	•	•	•	32A	115	90	70	35.7	42.7	15	2	12	33	4
•	•	•	•	•	40A	120	95	75	41.6	48.6	15	2	12	34	4
•	•	•	•	•	50A	130	105	85	52.9	60.5	15	2	14	36	4
•	•	•	•	•	65A	155	130	110	67.9	76.3	15	2	14	39	4
•	•	•	•	•	80A	180	145	121	80.7	89.1	19	2	14	41	4
•	•	•	•	•	90A	190	155	131	93.2	101.6	19	2	14	41	4
•	•	•	•	•	100A	200	165	141	105.3	114.3	19	2	16	41	8
•	•	•	•	•	125A	235	200	176	130.8	139.8	19	2	16	43	8
•	•	•	•	•	150A	265	230	206	155.2	165.2	19	2	18	49	8
•	•	•	•	•	200A	320	280	252	204.7	216.3	23	2	20	53	8
•	•	•	•	•	250A	385	345	317	254.2	267.4	23	2	22	61	12
	•	•	•	•	300A	430	390	360	304.7	318.5	23	3	22	62	12
			•	•	350A	480	435	403	339.8	355.6	25	3	24	73	12
			•	•	400A	540	495	463	390.6	406.4	25	3	24	76	16
				•	450A	605	555	523	441.4	457.2	25	3	24	79	16
				•	500A	655	605	573	492.2	508.0	25	3	24	79	20

