

Concentric Reducer

Valex Standard, JIS Pipe

Product Lines					Dimensions in Millimeters							
401	LDEP	201	101	CFOS	Size	O.D. 1	5S Wall	10S Wall	O.D. 2	5S Wall	10S Wall	A
•					10A x 8A	17.3	1.2	1.65	13.8	1.2	1.65	90
•		•	•		15A x 8A	21.7	1.65	2.1	13.8	1.2	1.65	100
•		•	•		15A x 10A	21.7	1.65	2.1	17.3	1.2	1.65	100
•		•	•		20A x 8A	27.2	1.65	2.1	13.8	1.2	1.65	105
•		•	•		20A x 10A	27.2	1.65	2.1	17.3	1.2	1.65	105
•		•	•		20A x 15A	27.2	1.65	2.1	21.7	1.65	2.1	105
•	•	•	•	•	25A x 8A	34.0	1.65	2.8	13.8	1.2	1.65	120
•	•	•	•	•	25A x 10A	34.0	1.65	2.8	17.3	1.2	1.65	120
•	•	•	•	•	25A x 15A	34.0	1.65	2.8	21.7	1.65	2.1	120
•	•	•	•	•	25A x 20A	34.0	1.65	2.8	27.2	1.65	2.1	120
•	•	•	•	•	32A x 15A	42.7	1.65	2.8	21.7	1.65	2.1	125
•	•	•	•	•	32A x 20A	42.7	1.65	2.8	27.2	1.65	2.1	125
•	•	•	•	•	32A x 25A	42.7	1.65	2.8	34.0	1.65	2.8	125
•	•	•	•	•	40A x 15A	48.6	1.65	2.8	21.7	1.65	2.1	130
•	•	•	•	•	40A x 20A	48.6	1.65	2.8	27.2	1.65	2.1	130
•	•	•	•	•	40A x 25A	48.6	1.65	2.8	34.0	1.65	2.8	130
•	•	•	•	•	40A x 32A	48.6	1.65	2.8	42.7	1.65	2.8	130
•	•	•	•	•	50A x 20A	60.5	1.65	2.8	27.2	1.65	2.1	140
•	•	•	•	•	50A x 25A	60.5	1.65	2.8	34.0	1.65	2.8	140
•	•	•	•	•	50A x 32A	60.5	1.65	2.8	42.7	1.65	2.8	140
•	•	•	•	•	50A x 40A	60.5	1.65	2.8	48.6	1.65	2.8	140
•	•	•	•	•	65A x 25A	76.3	2.1	3.0	34.0	1.65	2.8	165
•	•	•	•	•	65A x 32A	76.3	2.1	3.0	42.7	1.65	2.8	165
•	•	•	•	•	65A x 40A	76.3	2.1	3.0	48.6	1.65	2.8	165
•	•	•	•	•	65A x 50A	76.3	2.1	3.0	60.5	1.65	2.8	165
•	•	•	•	•	80A x 32A	89.1	2.1	3.0	42.7	1.65	2.8	170
•	•	•	•	•	80A x 40A	89.1	2.1	3.0	48.6	1.65	2.8	170
•	•	•	•	•	80A x 50A	89.1	2.1	3.0	60.5	1.65	2.8	170
•	•	•	•	•	80A x 65A	89.1	2.1	3.0	76.3	2.1	3.0	170
•	•	•	•	•	100A x 40A	114.3	2.1	3.0	48.6	1.65	2.8	180
•	•	•	•	•	100A x 50A	114.3	2.1	3.0	60.5	1.65	2.8	180
•	•	•	•	•	100A x 65A	114.3	2.1	3.0	76.3	2.1	3.0	180
•	•	•	•	•	100A x 80A	114.3	2.1	3.0	89.1	2.1	3.0	180
•	•	•	•	•	125A x 50A	139.8	2.8	3.4	60.5	1.65	2.8	250
•	•	•	•	•	125A x 65A	139.8	2.8	3.4	76.3	2.1	3.0	250
•	•	•	•	•	125A x 80A	139.8	2.8	3.4	89.1	2.1	3.0	250
•	•	•	•	•	125A x 100A	139.8	2.8	3.4	114.3	2.1	3.0	250
•	•	•	•	•	150A x 65A	216.3	2.8	3.4	76.3	2.1	3.0	260
•	•	•	•	•	150A x 80A	216.3	2.8	3.4	89.1	2.1	3.0	260
•	•	•	•	•	150A x 100A	216.3	2.8	3.4	114.3	2.1	3.0	260
•	•	•	•	•	150A x 125A	216.3	2.8	3.4	139.8	2.8	3.4	260
•	•	•	•	•	200A x 100A	216.3	2.8	4.0	114.3	2.1	3.0	280
•	•	•	•	•	200A x 125A	216.3	2.8	4.0	139.8	2.8	3.4	280
•	•	•	•	•	200A x 150A	216.3	2.8	4.0	165.2	2.8	3.4	280

