



Reducing Tee

JIS B2312 Standard, JIS Pipe

Product Lines					Dimensions in Millimeters								
401	LDEP	201	101	CFOS	Size	O.D. 1	5S Wall	10S Wall	O.D. 2	5S Wall	10S Wall	A	B
*		*	*		20A x 15A	27.2	1.65	2.1	21.7	1.65	2.1	28.6	28.6
*		*	*		25A x 15A	34.0	1.65	2.8	21.7	1.65	2.1	38.1	38.1
*		*	*		25A x 20A	34.0	1.65	2.8	27.2	1.65	2.1	38.1	38.1
*		*	*		32A x 15A	42.7	1.65	2.8	21.7	1.65	2.1	47.6	47.6
*		*	*		32A x 20A	42.7	1.65	2.8	27.2	1.65	2.1	47.6	47.6
*	*	*	*	*	32A x 25A	42.7	1.65	2.8	34.0	1.65	2.8	47.6	47.6
*		*	*		40A x 15A	48.6	1.65	2.8	21.7	1.65	2.1	57.2	57.2
*		*	*		40A x 20A	48.6	1.65	2.8	27.2	1.65	2.1	57.2	57.2
*	*	*	*	*	40A x 25A	48.6	1.65	2.8	34.0	1.65	2.8	57.2	57.2
*	*	*	*	*	40A x 32A	48.6	1.65	2.8	42.7	1.65	2.8	57.2	57.2
*		*	*		50A x 20A	60.5	1.65	2.8	27.2	1.65	2.1	63.5	44.5
*		*	*	*	50A x 25A	60.5	1.65	2.8	34.0	1.65	2.8	63.5	50.8
*	*	*	*	*	50A x 32A	60.5	1.65	2.8	42.7	1.65	2.8	63.5	57.2
*	*	*	*	*	50A x 40A	60.5	1.65	2.8	48.6	1.65	2.8	63.5	60.3
*	*	*	*	*	65A x 25A	76.3	2.1	3.0	34.0	1.65	2.8	76.2	57.2
*	*	*	*	*	65A x 32A	76.3	2.1	3.0	42.7	1.65	2.8	76.2	63.5
*	*	*	*	*	65A x 40A	76.3	2.1	3.0	48.6	1.65	2.8	76.2	66.7
*	*	*	*	*	65A x 50A	76.3	2.1	3.0	60.5	1.65	2.8	76.2	69.9
*	*	*	*	*	80A x 32A	89.1	2.1	3.0	42.7	1.65	2.8	85.7	69.9
*	*	*	*	*	80A x 40A	89.1	2.1	3.0	48.6	1.65	2.8	85.7	73.0
*	*	*	*	*	80A x 50A	89.1	2.1	3.0	60.5	1.65	2.8	85.7	76.2
*	*	*	*	*	80A x 65A	89.1	2.1	3.0	76.3	2.1	3.0	85.7	82.6
*	*	*	*	*	90A x 40A	101.6	2.1	3.0	48.6	1.65	2.8	95.3	79.4
*	*	*	*	*	90A x 50A	101.6	2.1	3.0	60.5	1.65	2.8	95.3	82.6
*	*	*	*	*	90A x 65A	101.6	2.1	3.0	76.3	2.1	3.0	95.3	88.9
*	*	*	*	*	90A x 80A	101.6	2.1	3.0	89.1	2.1	3.0	95.3	92.1
*	*	*	*	*	100A x 40A	114.3	2.1	3.0	48.6	1.65	2.8	104.8	85.7
*	*	*	*	*	100A x 50A	114.3	2.1	3.0	60.5	1.65	2.8	104.8	88.9
*	*	*	*	*	100A x 65A	114.3	2.1	3.0	76.3	2.1	3.0	104.8	95.3
*	*	*	*	*	100A x 80A	114.3	2.1	3.0	89.1	2.1	3.0	104.8	98.4
*	*	*	*	*	100A x 90A	114.3	2.1	3.0	101.6	2.1	3.0	104.8	101.6
*	*	*	*	*	125A x 50A	139.8	2.8	3.4	60.5	1.65	2.8	123.8	104.8
*	*	*	*	*	125A x 65A	139.8	2.8	3.4	76.3	2.1	3.0	123.8	108.0
*	*	*	*	*	125A x 80A	139.8	2.8	3.4	89.1	2.1	3.0	123.8	111.1
*	*	*	*	*	125A x 90A	139.8	2.8	3.4	101.6	2.1	3.0	123.8	114.3
*	*	*	*	*	125A x 100A	139.8	2.8	3.4	114.3	2.1	3.0	123.8	117.5
*	*	*	*	*	150A x 65A	165.2	2.8	3.4	76.3	2.1	3.0	142.9	120.7
*	*	*	*	*	150A x 80A	165.2	2.8	3.4	89.1	2.1	3.0	142.9	123.8
*	*	*	*	*	150A x 90A	165.2	2.8	3.4	101.6	2.1	3.0	142.9	127.0
*	*	*	*	*	150A x 100A	165.2	2.8	3.4	114.3	2.1	3.0	142.9	130.2
*	*	*	*	*	150A x 125A	165.2	2.8	3.4	139.8	2.8	3.4	142.9	136.5
*	*	*	*	*	200A x 90A	216.3	2.8	4.0	101.6	2.1	3.0	177.8	152.4
*	*	*	*	*	200A x 100A	216.3	2.8	4.0	114.3	2.1	3.0	177.8	155.6
*	*	*	*	*	200A x 125A	216.3	2.8	4.0	139.8	2.8	3.4	177.8	161.9
*	*	*	*	*	200A x 150A	216.3	2.8	4.0	165.2	2.8	3.4	177.8	168.3
*	*	*	*	*	250A x 100A	267.4	3.4	4.0	114.3	2.1	3.0	215.9	184.2
*	*	*	*	*	250A x 125A	267.4	3.4	4.0	139.8	2.8	3.4	215.9	190.5
*	*	*	*	*	250A x 150A	267.4	3.4	4.0	165.2	2.8	3.4	215.9	193.7
*	*	*	*	*	250A x 200A	267.4	3.4	4.0	216.3	2.8	4.0	215.9	203.2
*	*	*	*	*	300A x 125A	318.5	4.0	4.5	139.8	2.8	3.4	254.0	215.9
*	*	*	*	*	300A x 150A	318.5	4.0	4.5	165.2	2.8	3.4	254.0	219.1
*	*	*	*	*	300A x 200A	318.5	4.0	4.5	216.3	2.8	4.0	254.0	228.6
*	*	*	*	*	300A x 250A	318.5	4.0	4.5	267.4	3.4	4.0	254.0	241.3
*	*	*	*	*	350A x 150A	355.6	4.0	5.0	165.2	2.8	3.4	279.4	238.1
*	*	*	*	*	350A x 200A	355.6	4.0	5.0	216.3	2.8	4.0	279.4	247.7
*	*	*	*	*	350A x 250A	355.6	4.0	5.0	267.4	3.4	4.0	279.4	257.2
*	*	*	*	*	350A x 300A	355.6	4.0	5.0	318.5	4.0	4.5	279.4	269.9

•	•	400A x 150A	406.4	4.5	5.0	165.2	2.8	3.4	304.8	263.5
•	•	400A x 200A	406.4	4.5	5.0	216.3	2.8	4.0	304.8	273.1
•	•	400A x 250A	406.4	4.5	5.0	267.4	3.4	4.0	304.8	282.6
•	•	400A x 300A	406.4	4.5	5.0	318.5	4.0	4.5	304.8	295.3
•	•	400A x 350A	406.4	4.5	5.0	355.6	4.0	5.0	304.8	304.8
•	•	450A x 200A	457.2	4.5	5.0	216.3	2.8	4.0	342.9	298.5
•	•	450A x 250A	457.2	4.5	5.0	267.4	3.4	4.0	342.9	308.0
•	•	450A x 300A	457.2	4.5	5.0	318.5	4.0	4.5	342.9	320.7
•	•	450A x 350A	457.2	4.5	5.0	355.6	4.0	5.0	342.9	330.2
•	•	450A x 400A	457.2	4.5	5.0	406.4	4.5	5.0	342.9	330.2
•	•	500A x 200A	508.0	5.0	5.5	216.3	2.8	4.0	381.0	323.9
•	•	500A x 250A	508.0	5.0	5.5	267.4	3.4	4.0	381.0	333.4
•	•	500A x 300A	508.0	5.0	5.5	318.5	4.0	4.5	381.0	346.1
•	•	500A x 350A	508.0	5.0	5.5	355.6	4.0	5.0	381.0	355.6
•	•	500A x 400A	508.0	5.0	5.5	406.4	4.5	5.0	381.0	355.6
•	•	500A x 450A	508.0	5.0	5.5	457.2	4.5	5.0	381.0	368.3

