



Material Type:	Nickel-Chromium-Molybdenum Alloy UNS Designation N06022
Dimensions:	ASTM Tube Sizes: • 1/4" to 1/2" (6.35mm to 12.7mm)
Reference Documents:	ASTM: B 622
Tube Lengths:	• 18.5-feet to 20.083-feet (5.64-meters to 6.121-meters)
Manufacturing Method:	Seamless
Tolerances:	Outside Diameter: ±.005" Wall Thickness: ±12.5%
I.D. Surface Roughness:	• 20 micro-inches (.51 micro-meters) Ra max.
Weld Ends:	Square ends suitable for orbital welding
Testing & Inspection:	<ul style="list-style-type: none"> • Visual inspection • Surface roughness measurement • Helium-leak test • Dimensional inspection
Marking & Traceability:	Each component is traceable to its producing mill and heat by an identification number etched within 24" (610mm) of one end.
Labeling:	Each component's bag is affixed with a label identifying the component's part number, date and Valex lot number.
Documentation:	A Quality Inspection Certificate is furnished with each shipment. The report contains the following information: <ul style="list-style-type: none"> a. Material composition & applicable specification designation b. Nominal outside diameter size c. Chemical composition d. Statement of quality assurance testing e. Inspection Certificate type 3.1 per EN 10204:2004 f. Lot & heat identification for traceability
Packaging:	All tube and fittings are purged with UHP nitrogen, capped, bagged and packaged for shipment in such a manner which prevents damage to product and primary-product packaging.

* HASTELLOY and C-22 are registered trademarks of Haynes International Inc.