

CONFIGURATION
38LJ
 USE WITH
 38LA/38SA

Lap Joint Flange

ASME B16.5 Standard, Class 150

| Product Lines | Dimensions in Inches | | | | | | | | | |
|---------------|----------------------|-----------|-------|-------|-------|-------|------|------|-----|------------|
| | CFOS | Size | A | B | C | D | E | F | R | # of Bolts |
| • | | NPS 1/2 | 3.50 | 2.38 | .90 | .625 | .38 | .62 | .12 | 4 |
| • | | NPS 3/4 | 3.88 | 2.75 | 1.11 | .625 | .44 | .62 | .12 | 4 |
| • | | NPS 1 | 4.25 | 3.12 | 1.38 | .625 | .50 | .69 | .12 | 4 |
| • | | NPS 1-1/4 | 4.62 | 3.50 | 1.72 | .625 | .56 | .81 | .19 | 4 |
| • | | NPS 1-1/2 | 5.00 | 3.88 | 1.97 | .625 | .62 | .88 | .25 | 4 |
| • | | NPS 2 | 6.00 | 4.75 | 2.46 | .750 | .69 | 1.00 | .31 | 4 |
| • | | NPS 2-1/2 | 7.00 | 5.50 | 2.97 | .750 | .81 | 1.12 | .31 | 4 |
| • | | NPS 3 | 7.50 | 6.00 | 3.60 | .750 | .88 | 1.19 | .38 | 4 |
| • | | NPS 3-1/2 | 8.50 | 7.00 | 4.10 | .750 | .88 | 1.25 | .38 | 8 |
| • | | NPS 4 | 9.00 | 7.50 | 4.60 | .750 | .88 | 1.31 | .44 | 8 |
| • | | NPS 5 | 10.00 | 8.50 | 5.69 | .875 | .88 | 1.44 | .44 | 8 |
| • | | NPS 6 | 11.00 | 9.50 | 6.75 | .875 | .94 | 1.56 | .50 | 8 |
| • | | NPS 8 | 13.50 | 11.75 | 8.75 | .875 | 1.06 | 1.75 | .50 | 8 |
| • | | NPS 10 | 16.00 | 14.25 | 10.92 | 1.000 | 1.12 | 1.94 | .50 | 12 |
| • | | NPS 12 | 19.00 | 17.00 | 12.92 | 1.000 | 1.19 | 2.19 | .50 | 12 |
| • | | NPS 14 | 21.00 | 18.75 | 14.18 | 1.125 | 1.31 | 3.12 | .50 | 12 |
| • | | NPS 16 | 23.50 | 21.25 | 16.19 | 1.125 | 1.38 | 3.44 | .50 | 16 |
| • | | NPS 18 | 25.00 | 22.75 | 18.20 | 1.250 | 1.50 | 3.81 | .50 | 16 |
| • | | NPS 20 | 27.50 | 25.00 | 20.25 | 1.250 | 1.62 | 4.06 | .50 | 20 |

