

CONFIGURATION
38WN

Weld Neck Flange

JIS B2220 Standard, Nominal Pressure 10K

Product Lines					Dimensions in Millimeters										
401	LDEP	201	101	CFOS	Size	A	B	C	D	E	F	G	H	I	# of Bolts
•					10A	90	65	46	12.7	17.3	15	1	12	29	4
•		•	•		15A	95	70	51	16.1	21.7	15	1	12	31	4
•		•	•		20A	100	75	56	21.6	27.2	15	1	14	32	4
•	•	•	•	•	25A	125	90	67	27.6	34.0	19	1	14	36	4
•	•	•	•	•	32A	135	100	76	35.7	42.7	19	2	16	38	4
•	•	•	•	•	40A	140	105	81	41.6	48.6	19	2	16	38	4
•	•	•	•	•	50A	155	120	96	52.9	60.5	19	2	16	40	4
•	•	•	•	•	65A	175	140	116	67.9	76.3	19	2	18	44	4
•	•	•	•	•	80A	185	150	126	80.7	89.1	19	2	18	45	8
•	•	•	•	•	90A	195	160	136	93.2	101.6	19	2	18	45	8
•	•	•	•	•	100A	210	175	151	105.3	114.3	19	2	18	45	8
•	•	•	•	•	125A	250	210	182	130.8	139.8	23	2	20	47	8
•	•	•	•	•	150A	280	240	212	155.2	165.2	23	2	22	53	8
•	•	•	•	•	200A	330	290	262	204.7	216.3	23	2	22	58	12
•	•	•	•	•	250A	400	355	324	254.2	267.4	25	2	24	65	12
	•	•	•	•	300A	445	400	368	304.7	318.5	25	3	24	68	16
			•	•	350A	490	445	413	339.8	355.6	25	3	26	79	16
			•	•	400A	560	510	475	390.6	406.4	27	3	28	85	16
			•	•	450A	620	565	530	441.4	457.2	27	3	30	90	20
			•	•	500A	675	620	585	492.2	508.0	27	3	30	99	20

