

Note: Not all possible part number combinations are available. Please contact Valex for availability.
Statement of PED approval available upon request.

TUBE & NPS , JIS PIPE SIZES																																																															
S - STR 40 A XX X S S - M B																																																															
<p>Material S = Stainless Steel</p> <p>Assembly Pattern STR = straight DHC = double horizontal cross SHC = single horizontal cross DHT = double horizontal tee DVT = double vertical tee DAV = double angle valve DSS = double single sided</p> <p>Main Tube/Pipe Sizes</p> <table border="0"> <tr><td>04 = 1/4" o.d. x .035" wall</td><td>15 = DN15 (NPS 1/2 / JIS 15A)</td></tr> <tr><td>06 = 3/8" o.d. x .035" wall</td><td>20 = DN20 (NPS 3/4 / JIS 20A)</td></tr> <tr><td>08 = 1/2" o.d. x .049" wall</td><td>25 = DN25 (NPS 1 / JIS 25A)</td></tr> <tr><td>12 = 3/4" o.d. x .065" wall</td><td>32 = DN32 (NPS 1-1/4 / JIS 32A)</td></tr> <tr><td>16 = 1" o.d. x .065" wall</td><td>40 = DN40 (NPS 1-1/2 / JIS 40A)</td></tr> <tr><td>24 = 1-1/2" o.d. x .065" wall</td><td>50 = DN50 (NPS 2 / JIS 50A)</td></tr> <tr><td>32 = 2" o.d. x .065" wall</td><td>65 = DN65 (NPS 2-1/2 / JIS 65A)</td></tr> <tr><td>40 = 2-1/2" o.d. x .065" wall</td><td>80 = DN80 (NPS 3 / JIS 80A)</td></tr> <tr><td>48 = 3" o.d. x .065" wall</td><td>100 = DN100 (NPS 4 / JIS 100A)</td></tr> <tr><td>64 = 4" o.d. x .083" wall</td><td>150 = DN 150 (NPS 6 / JIS 150A)</td></tr> <tr><td>96 = 6" o.d. x .109" wall</td><td>200 = DN200 (NPS 8 / JIS 200A)</td></tr> <tr><td></td><td>250 = DN250 (NPS 10 / JIS 250A)</td></tr> <tr><td></td><td>300 = DN300 (NPS 12 / JIS 300A)</td></tr> <tr><td></td><td>350 = DN350 (NPS 14 / JIS 350A)</td></tr> </table> <p>Main Tube/Pipe Connections</p> <p>A = JIS (sch 5) pipe butt weld inlet/outlet B = tube butt weld inlet, tube butt weld outlet w/welded cap C = compression fitting inlet and outlet D = JIS (sch 10) pipe butt weld inlet/outlet E = tube butt weld inlet, FNPT outlet F = face-seal fixed male inlet and outlet G = tube butt weld inlet, face-seal fixed male outlet H = compression fitting inlet, tube butt weld outlet J = tube butt weld inlet, compression fitting outlet K = face-seal fixed male inlet, tube butt weld outlet L = NPS (sch 10) pipe butt weld inlet/outlet M = tube butt weld inlet and outlet N = tube butt weld inlet, B16.5 Class 150 Flange outlet P = B16.5 Class 150 Flange inlet and outlet Q = compression fitting w/plug inlet, tube butt weld outlet R = tube butt weld inlet, compression fitting w/plug outlet</p> <p>Branch Valve(s) Outlet Size</p> <table border="0"> <tr><td>04 = 1/4" o.d. x .035" wall</td><td>XX = no branch valve(s)</td></tr> <tr><td>06 = 3/8" o.d. x .035" wall</td><td>15 = DN15 (NPS 1/2 / JIS 15A)</td></tr> <tr><td>08 = 1/2" o.d. x .049" wall</td><td>20 = DN20 (NPS 3/4 / JIS 20A)</td></tr> <tr><td>12 = 3/4" o.d. x .065" wall</td><td>25 = DN25 (NPS 1 / JIS 25A)</td></tr> <tr><td>16 = 1" o.d. x .065" wall</td><td>32 = DN32 (NPS 1-1/4 / JIS 32A)</td></tr> <tr><td>24 = 1-1/2" o.d. x .065" wall</td><td>40 = DN40 (NPS 1-1/2 / JIS 50A)</td></tr> <tr><td>32 = 2" o.d. x .065" wall</td><td>50 = DN50 (NPS 2 / JIS 50A)</td></tr> <tr><td>40 = 2-1/2" o.d. x .065" wall</td><td>65 = DN65 (NPS 2-1/2 / JIS 65A)</td></tr> <tr><td>48 = 3" o.d. x .065" wall</td><td>80 = DN80 (NPS 3 / JIS 80A)</td></tr> <tr><td>64 = 4" o.d. x .083" wall</td><td>100 = DN100 (NPS 4 / JIS 100A)</td></tr> <tr><td>96 = 6" o.d. x .109" wall</td><td>150 = DN150 (NPS 6 / JIS 150A)</td></tr> </table>	04 = 1/4" o.d. x .035" wall	15 = DN15 (NPS 1/2 / JIS 15A)	06 = 3/8" o.d. x .035" wall	20 = DN20 (NPS 3/4 / JIS 20A)	08 = 1/2" o.d. x .049" wall	25 = DN25 (NPS 1 / JIS 25A)	12 = 3/4" o.d. x .065" wall	32 = DN32 (NPS 1-1/4 / JIS 32A)	16 = 1" o.d. x .065" wall	40 = DN40 (NPS 1-1/2 / JIS 40A)	24 = 1-1/2" o.d. x .065" wall	50 = DN50 (NPS 2 / JIS 50A)	32 = 2" o.d. x .065" wall	65 = DN65 (NPS 2-1/2 / JIS 65A)	40 = 2-1/2" o.d. x .065" wall	80 = DN80 (NPS 3 / JIS 80A)	48 = 3" o.d. x .065" wall	100 = DN100 (NPS 4 / JIS 100A)	64 = 4" o.d. x .083" wall	150 = DN 150 (NPS 6 / JIS 150A)	96 = 6" o.d. x .109" wall	200 = DN200 (NPS 8 / JIS 200A)		250 = DN250 (NPS 10 / JIS 250A)		300 = DN300 (NPS 12 / JIS 300A)		350 = DN350 (NPS 14 / JIS 350A)	04 = 1/4" o.d. x .035" wall	XX = no branch valve(s)	06 = 3/8" o.d. x .035" wall	15 = DN15 (NPS 1/2 / JIS 15A)	08 = 1/2" o.d. x .049" wall	20 = DN20 (NPS 3/4 / JIS 20A)	12 = 3/4" o.d. x .065" wall	25 = DN25 (NPS 1 / JIS 25A)	16 = 1" o.d. x .065" wall	32 = DN32 (NPS 1-1/4 / JIS 32A)	24 = 1-1/2" o.d. x .065" wall	40 = DN40 (NPS 1-1/2 / JIS 50A)	32 = 2" o.d. x .065" wall	50 = DN50 (NPS 2 / JIS 50A)	40 = 2-1/2" o.d. x .065" wall	65 = DN65 (NPS 2-1/2 / JIS 65A)	48 = 3" o.d. x .065" wall	80 = DN80 (NPS 3 / JIS 80A)	64 = 4" o.d. x .083" wall	100 = DN100 (NPS 4 / JIS 100A)	96 = 6" o.d. x .109" wall	150 = DN150 (NPS 6 / JIS 150A)	<p>Handle Sleeve Color</p> <table border="0"> <tr><td>O = N/A</td><td>N = brown</td></tr> <tr><td>B = blue</td><td>P = purple</td></tr> <tr><td>D = gold</td><td>R = red</td></tr> <tr><td>G = green</td><td>S = silver</td></tr> <tr><td>I = pink</td><td>W = white</td></tr> <tr><td>K = black</td><td>Y = yellow</td></tr> </table> <p>Section 9.0 Identifier</p> <p>E = 10 Ra electropolished L = 10 Ra electropolished, oxygen-compatible lube M = Standard Finish Option (per SP-9217)</p> <p>Outlet Purge Port*</p> <p>X = no purge port C = compression fitting D = purge drill (open to atmosphere) P = compression fitting w/plug S = face-seal (swivel male nut w/cap) T = purge tube (open to atmosphere) U = face-seal (swivel female nut w/plug) V = purge valve w/ compression fitting</p> <p>Inlet Purge Port*</p> <p>X = no purge port C = compression fitting D = purge drill (open to atmosphere) P = compression fitting w/plug S = face seal (swivel male nut w/cap) T = purge tube (open to atmosphere) U = face-seal (swivel female nut w/plug) V = purge valve w/compression fitting</p> <p>Connection On Branch Valves(s)</p> <p>X = no branch valve A = JIS (sch 5) pipe butt weld B = tube butt weld w/welded cap C = compression fitting D = NPS (sch 10) w/B16.5 Class 150 Flange E = female NPT national pipe thread F = face-seal fixed male L = NPS (sch 10) pipe butt weld M = tube butt weld P = compression fitting w/plug</p>	O = N/A	N = brown	B = blue	P = purple	D = gold	R = red	G = green	S = silver	I = pink	W = white	K = black	Y = yellow
04 = 1/4" o.d. x .035" wall	15 = DN15 (NPS 1/2 / JIS 15A)																																																														
06 = 3/8" o.d. x .035" wall	20 = DN20 (NPS 3/4 / JIS 20A)																																																														
08 = 1/2" o.d. x .049" wall	25 = DN25 (NPS 1 / JIS 25A)																																																														
12 = 3/4" o.d. x .065" wall	32 = DN32 (NPS 1-1/4 / JIS 32A)																																																														
16 = 1" o.d. x .065" wall	40 = DN40 (NPS 1-1/2 / JIS 40A)																																																														
24 = 1-1/2" o.d. x .065" wall	50 = DN50 (NPS 2 / JIS 50A)																																																														
32 = 2" o.d. x .065" wall	65 = DN65 (NPS 2-1/2 / JIS 65A)																																																														
40 = 2-1/2" o.d. x .065" wall	80 = DN80 (NPS 3 / JIS 80A)																																																														
48 = 3" o.d. x .065" wall	100 = DN100 (NPS 4 / JIS 100A)																																																														
64 = 4" o.d. x .083" wall	150 = DN 150 (NPS 6 / JIS 150A)																																																														
96 = 6" o.d. x .109" wall	200 = DN200 (NPS 8 / JIS 200A)																																																														
	250 = DN250 (NPS 10 / JIS 250A)																																																														
	300 = DN300 (NPS 12 / JIS 300A)																																																														
	350 = DN350 (NPS 14 / JIS 350A)																																																														
04 = 1/4" o.d. x .035" wall	XX = no branch valve(s)																																																														
06 = 3/8" o.d. x .035" wall	15 = DN15 (NPS 1/2 / JIS 15A)																																																														
08 = 1/2" o.d. x .049" wall	20 = DN20 (NPS 3/4 / JIS 20A)																																																														
12 = 3/4" o.d. x .065" wall	25 = DN25 (NPS 1 / JIS 25A)																																																														
16 = 1" o.d. x .065" wall	32 = DN32 (NPS 1-1/4 / JIS 32A)																																																														
24 = 1-1/2" o.d. x .065" wall	40 = DN40 (NPS 1-1/2 / JIS 50A)																																																														
32 = 2" o.d. x .065" wall	50 = DN50 (NPS 2 / JIS 50A)																																																														
40 = 2-1/2" o.d. x .065" wall	65 = DN65 (NPS 2-1/2 / JIS 65A)																																																														
48 = 3" o.d. x .065" wall	80 = DN80 (NPS 3 / JIS 80A)																																																														
64 = 4" o.d. x .083" wall	100 = DN100 (NPS 4 / JIS 100A)																																																														
96 = 6" o.d. x .109" wall	150 = DN150 (NPS 6 / JIS 150A)																																																														
O = N/A	N = brown																																																														
B = blue	P = purple																																																														
D = gold	R = red																																																														
G = green	S = silver																																																														
I = pink	W = white																																																														
K = black	Y = yellow																																																														
	<p>* Purge port sizes 1/4" purge port is used for valve sizes up to 2" Tube & DN50 Pipe (NPS 2 / JIS 50A). 1/2" purge port is used for valve sizes larger than 2" & DN50 Pipe (NPS 2 / JIS 50A).</p>																																																														