

VACUUM TUBE & PIPE PART NUMBER MATRIX

XX

- XXXXX

X

X

XXXX

- XXXX

PROCESS / ALLOY^{1&2}

CW = 316L WELDED
DW = 304L WELDED

SIZE CODE:

<u>ASTM TUBE O.D.</u>	<u>NPS PIPE O.D.</u>
1/4 = .25"	300 = DN 300 (NPS 12 / JIS 300A)
3/8 = .375"	
1/2 = .5"	
3/4 = .75"	
1 = 1"	
1-1/2 = 1.5"	
2 = 2"	
2-1/2 = 2.5"	
3 = 3"	
4 = 4"	
6 = 6"	
8 = 8"	
10 = 10"	

END TYPE CODE:

ASTM TUBE
BLANK = SQUARE

NPS PIPE:
L = SQUARE

WALL CODE

<u>TUBE WALL THICKNESS</u>	<u>PIPE SCHEDULE</u>
.035 = .035"	10S = SCH. 10
.039 = .039"	
.049 = .049"	
.065 = .065"	
.083 = .083"	
.120 = .120"	

FINISH CODE^{3&4}

MP = O.D.=150-grit MP, I.D.=180-grit MP
VB = O.D.=BA/AP, I.D.=BA/AP

ASTM Tube Example:

CW-1/2X.049-VB
 VALEX VACUUM SPEC TUBE, 316L WELDED, 1/2" O.D. X .049" WALL,
 VB FINISH OPTION, SQUARED ENDS

NPS Pipe Example:

DW-300LX10S-VB
 VALEX VACUUM SPEC PIPE, 304L WELDED, NPS 12 (DN 300) X SCH 10,
 VB FINISH OPTION, SQUARED ENDS

NOTES:

- PER VALEX SPECIFICATION SP-7201
- PROCESS CODES ARE NOT AVAILABLE FOR ALL SIZE AND FINISH CODES. PLEASE CONTACT VALEX FOR ITEM NUMBER AVAILABILITY.
- VB FINISH CODE: BA FOR SIZES < 6" AND AP FOR SIZES ≥ 6".
- FOR EP GRADE, REFER TO 401 PRODUCT LINE



www.valex.com

TITLE		
VACUUM FITTINGS & HOSE ITEM NUMBER SCHEME		
SPECIFICATION	SHEET	REV.
SP-7200	1/4	O

VACUUM FITTING PART NUMBER MATRIX

<p>XX</p> <p>MATERIAL / FINISH</p> <p>STANDARD FINISH SS¹</p> <p>VA = 304 VD = 304L VC = 316L VQ = 316LN</p> <p>MECHANICAL POLISHED SS</p> <p>VE = 304 VH = 304L VG = 316L</p> <p>ELECTROPOLISHED SS</p> <p>VK = 304 EP VN = 304L EP VM = 316L EP</p>	<p>- XXX</p> <p>CONFIGURATION CODE</p> <p>2 = 90° ELBOW, WITH TANGENT 2T = 90° ELBOW, NO TANGENT 2L = 90° ELBOW, EXTENDED TANGENT 2M = 90° ELBOW, MITERED NO TANGENT 2X = 90° ELBOW, MITERED EXTENDED 2K = 45° ELBOW, WITH TANGENT 2N = 45° ELBOW, NO TANGENT</p> <p>3Y = Y BRANCH</p> <p>6HS = NIPPLE, HALF, SHORT 6H = NIPPLE, HALF 6HE = NIPPLE, HALF, EXTENDED 6F = NIPPLE, FULL 6FE = NIPPLE, FULL, EXTENDED</p> <p>7 = TEE, EQUAL 7L = TEE, EQUAL, EXTENDEND 7R = TEE, REDUCING</p> <p>9 = CROSS, 4-WAY 9R = CROSS, 4-WAY REDUCING 9L = CROSS, 4-WAY, EXTENDED 9F = CROSS, 5-WAY 9E = CROSS, 5-WAY, EXTENDED 9S = CROSS, 6-WAY 9T = CROSS, 6-WAY, EXTENDED 9C = CROSS, 6-WAY CUBE</p> <p>16 = CAP, WELD 31 = REDUCER, CONCENTRIC / CONICAL 31T = REDUCER, CONCENTRIC W/ TANGENT 31L = REDUCER, STRAIGHT</p> <p>34 = ADAPTER, CONCENTRIC / CONICAL 34L = ADAPTER, CONCENTRIC LOW PROFILE 34T = ADAPTER, CONCENTRIC W/ TANGENT 34S = ADAPTER, STRAIGHT 34V = ADAPTOR, FACE SEAL MALE 34A = ADAPTOR, FACE SEAL FEMALE 34C = ADAPTOR, COMPRESSION 34M = ADAPTOR, NPT MALE 34F = ADAPTOR, NPT FEMALE 34H = ADAPTOR, HOSE 34G = ADAPTOR, GAUGE TEE</p> <p>38 = FLANGE, BLANK 38W = FLANGE, BLANK, NECK WELD 38Q = FLANGE, BLANK, NECK WELD W/ WELD PREP 38D = FLANGE, BLANK, DOUBLE SIDED 38B = FLANGE, BORED 38S = FLANGE, BORED, SOCKET WELD 38N = FLANGE, BORED, SHORT NECK WELD 38L = FLANGE, BORED, LONG NECK WELD 38K = FLANGE, BORED, NECK WELD 38V = FLANGE, BORED, NECK WELD W/ WELD PREP 38M = FLANGE, BORED, DOUBLE SIDED 38Z = FLANGE, BORED, ZERO LENGTH REDUCER</p>
--	--

<p>- X</p> <p>TYPE CODE</p> <p>CONNECTION TYPE</p> <p>W = WELD (BUTTWELD/SOCKET) Z = FITTING SIZE (NPT, HOSE, FACE-SEAL, COMPRESSION)</p> <p>FLANGE TYPE</p> <p>N = NW / KF K = ISO-K F = ISO-F (BOLTED) C = CF</p>
--

<p>XX</p> <p>SIZE CODE</p> <p>TUBE / PIPE / FITTING</p> <table border="0" style="width: 100%;"> <tr> <th style="text-align: left;">TUBE, FITTING O.D.</th> <th style="text-align: left;">PIPE O.D.</th> </tr> <tr> <td>02 = 1/8"</td> <td>67 = 1/8 NPS / NPT</td> </tr> <tr> <td>04 = 1/4"</td> <td>68 = 1/4 NPS / NPT</td> </tr> <tr> <td>06 = 3/8"</td> <td>69 = 3/8 NPS / NPT</td> </tr> <tr> <td>08 = 1/2"</td> <td>70 = 1/2 NPS / NPT</td> </tr> <tr> <td>10 = 5/8"</td> <td>71 = 3/4 NPS / NPT</td> </tr> <tr> <td>12 = 3/4"</td> <td>72 = 1 NPS / NPT</td> </tr> <tr> <td>14 = 7/8"</td> <td>74 = 1-1/2 NPS / NPT</td> </tr> <tr> <td>16 = 1"</td> <td>75 = 2 NPT</td> </tr> <tr> <td>20 = 1-1/4"</td> <td>76 = 2-1/2 NPT</td> </tr> <tr> <td>24 = 1-1/2"</td> <td>77 = 3 NPT</td> </tr> <tr> <td>26 = 1-5/8"</td> <td>79 = 4 NPT</td> </tr> <tr> <td>28 = 1-3/4"</td> <td>81 = 6 NPT</td> </tr> <tr> <td>32 = 2"</td> <td>84 = 12 NPS (12.75")</td> </tr> <tr> <td>40 = 2-1/2"</td> <td></td> </tr> <tr> <td>48 = 3"</td> <td></td> </tr> <tr> <td>64 = 4"</td> <td></td> </tr> <tr> <td>80 = 5"</td> <td></td> </tr> <tr> <td>96 = 6"</td> <td></td> </tr> <tr> <td>53 = 8"</td> <td></td> </tr> <tr> <td>55 = 10"</td> <td></td> </tr> <tr> <td>57 = 12"</td> <td></td> </tr> </table>	TUBE, FITTING O.D.	PIPE O.D.	02 = 1/8"	67 = 1/8 NPS / NPT	04 = 1/4"	68 = 1/4 NPS / NPT	06 = 3/8"	69 = 3/8 NPS / NPT	08 = 1/2"	70 = 1/2 NPS / NPT	10 = 5/8"	71 = 3/4 NPS / NPT	12 = 3/4"	72 = 1 NPS / NPT	14 = 7/8"	74 = 1-1/2 NPS / NPT	16 = 1"	75 = 2 NPT	20 = 1-1/4"	76 = 2-1/2 NPT	24 = 1-1/2"	77 = 3 NPT	26 = 1-5/8"	79 = 4 NPT	28 = 1-3/4"	81 = 6 NPT	32 = 2"	84 = 12 NPS (12.75")	40 = 2-1/2"		48 = 3"		64 = 4"		80 = 5"		96 = 6"		53 = 8"		55 = 10"		57 = 12"	
TUBE, FITTING O.D.	PIPE O.D.																																											
02 = 1/8"	67 = 1/8 NPS / NPT																																											
04 = 1/4"	68 = 1/4 NPS / NPT																																											
06 = 3/8"	69 = 3/8 NPS / NPT																																											
08 = 1/2"	70 = 1/2 NPS / NPT																																											
10 = 5/8"	71 = 3/4 NPS / NPT																																											
12 = 3/4"	72 = 1 NPS / NPT																																											
14 = 7/8"	74 = 1-1/2 NPS / NPT																																											
16 = 1"	75 = 2 NPT																																											
20 = 1-1/4"	76 = 2-1/2 NPT																																											
24 = 1-1/2"	77 = 3 NPT																																											
26 = 1-5/8"	79 = 4 NPT																																											
28 = 1-3/4"	81 = 6 NPT																																											
32 = 2"	84 = 12 NPS (12.75")																																											
40 = 2-1/2"																																												
48 = 3"																																												
64 = 4"																																												
80 = 5"																																												
96 = 6"																																												
53 = 8"																																												
55 = 10"																																												
57 = 12"																																												

<p>NW / KF FLANGE³</p> <p>1A = NW 10 (1.18", 30mm O.D.) 1B = NW 16 (1.18", 30mm O.D.) 1C = NW 25 (1.58", 40mm O.D.) 1D = NW 40 (2.16", 55mm O.D.) 1E = NW 50 (2.95", 75mm O.D.) 1F = NW 20 (1.58", 40mm O.D.) 1G = NW 32 (2.16", 55mm O.D.) 1H = NW 80 (4.33", 110mm O.D.) 1J = NW 100 (5.12", 130mm O.D.) 1K = NW 160 (7.09", 180mm O.D.)</p>
--

<p>ISO FLANGE</p> <p>2A = ISO63 (3.74", 95mm O.D.) 2B = ISO80 (4.33", 110mm O.D.) 2C = ISO100 (5.12", 130mm O.D.) 2D = ISO160 (7.09", 180mm O.D.) 2E = ISO200 (9.45", 240mm O.D.) 2F = ISO250 (11.42", 290mm O.D.) 2G = ISO320 (14.75", 370mm O.D.) 2H = ISO400 (17.72", 450mm O.D.) 2J = ISO500 (21.65", 550mm O.D.)</p>
--

<p>CF FLANGE</p> <p>3A = 1.33" (1.33", 33.8mm O.D.) 3B = 2.12" (2.12", 53.8mm O.D.) 3C = 2.75" (2.73", 69.3mm O.D.) 3D = 3.38" (3.36", 85.3mm O.D.) 3E = 4.50" (4.47", 113.5mm O.D.) 3F = 4.62" (4.61", 117.1mm O.D.) 3G = 6.00" (5.97", 151.6mm O.D.) 3H = 6.75" (6.73", 170.9mm O.D.) 3J = 8.00" (7.97", 202.4mm O.D.) 3K = 10.00" (9.97", 253.2mm O.D.) 3L = 12.00" (11.97", 304.0mm O.D.) 3M = 13.25" (13.25", 336.6mm O.D.) 3N = 14.00" (14.00", 355.6mm O.D.) 3P = 14.50" (14.50", 368.3mm O.D.) 3Q = 16.50" (16.50", 419.1mm O.D.)</p>
--

<p>NW / KF FLANGE (CHAIN CLAMP)⁴</p> <p>5H = NW 80 (4.33", 110mm O.D.) 5J = NW 100 (5.12", 130mm O.D.) 5K = NW 160 (7.09", 180mm O.D.)</p>
--

<p>x X XX</p> <p>TYPE SIZE</p> <p>USED FOR 2ND SIZE: FLANGE, BUTTWELD/SOCKET WELD, OR FITTING</p> <p><i>If required, build second size by using two previous columns (type & size code)</i></p> <p>EX: VA-7-W12XW08 VA-34M-K2AXK2A VA-38B-N1BXW06</p>
--

<p>- XX</p> <p>ATTRIBUTE CODE</p> <p>OTHER</p> <p>BLANK = Configurations not listed below <i>(Note: for BLANK code, do not include -XX in part number)</i></p> <p>ONLY USE FOR CF & ISO-F FLANGES</p> <p>FF = NON-ROTATABLE FS = NON-ROTATABLE, TAPPED, INCH FM = NON-ROTATABLE, TAPPED, METRIC FR = ROTATABLE FT = ROTATABLE, TAPPED, INCH FN = ROTATABLE, TAPPED, METRIC</p> <p>ONLY USE FOR: CF FLANGED TEES, CF CROSSES, CF REDUCERS, CF HALF & CF FULL NIPPLES</p> <p>TA = NON-ROTATABLE, ROTATABLE TB = NON-ROTATABLE, 2 ROTATABLE TC = 2 NON-ROTATABLE, 2 ROTATABLE TD = 2 NON-ROTATABLE, 3 ROTATABLE TE = 3 NON-ROTATABLE, 3 ROTATABLE TF = NON-ROTATABLE TG = ROTATABLE</p>
--

- NOTES:**
- STANDARD FINISH IS TUMBLE FOR BUTTWELD FITTINGS.
 - STANDARD FINISH IS MACHINED FOR FLANGES.
 - FLANGE SIZES 1H, 1J, & 1K USE WITH BAND CLAMP
 - FLANGE SIZES 5H, 5J, & 5K USE WITH CHAIN CLAMP
 - NOT ALL POSSIBLE PART NUMBER CONFIGURATION ARE AVAILABLE. PLEASE CONTACT VALEX FOR AVAILABILITY.

- Part Number Examples:*
- Elbow: VA-2-N1D
Concentric Reducer: VA-31-N1DXN1B
Full Nipple: VA-6F-N1E
Straight Reducer: VA-31L-K2BXK2A
Equal Tee: VA-7-K2AXK2A
Reducing Tee: VA-7R-K2CXK2A
4-Way Reducing Cross: VA-9R-C3DXC3A-TC
Adaptor, FACE-SEAL MALE: VA-34V-C3AXZ04-FF
Adaptor Concentric Reducer: VA-34-K2AXN1D
Blank Flange: VA-38-N1A
Bored Flange Rotatable: VA-38B-C3HXW80-FR
Zero Length Reducer: VA-38Z-C3GXC3A-FF

<p>TITLE: VACUUM FITTINGS & HOSE ITEM NUMBER SCHEME</p>		
<p>SPECIFICATION: SP-7200</p>	<p>SHEET: 2 OF 4</p>	<p>REV: O</p>

VACUUM ACCESSORIES PART NUMBER MATRIX

XX MATERIAL / FINISH	- XXX CONFIGURATION CODE	- X TYPE CODE	XX SIZE CODE	x XX SIZE USED FOR REDUCING CENTERING RING <i>If required, build 2nd size by using previous column (size code)</i> EX: V0-39L-N1FX1C-4CX	- XX (XX) ATTRIBUTE CODE
<p>OTHER MATERIALS</p> <p>V0 = USE FOR: CLAMPS, CAPS, RINGS, GASKETS, O-RINGS, & HARDWARE</p>	<p>13 = CLAMP, SINGLE CLAW 13D = CLAMP, DOUBLE CLAW 13W = CLAMP, WING NUT 13L = CLAMP, LEVER / QUICK 13C = CLAMP, CHAIN 13B = CLAMP, BULKHEAD 13T = CLAMP, TOGGLE 16D = CAP, PLASTIC DUST</p> <hr/> <p>39 = RING, CENTERING 39C = RING, CENTERING W/ O-RING ASSEMBLY 39M = RING, CENTERING, SCREEN W/ O-RING ASSEMBLY 39N = RING, CENTERING, SCREEN W/ O-RING & SPACER RING ASSEMBLY 39S = RING, SPACER 39D = RING, CENTERING W/ O-RING & SPACER RING ASSEMBLY 39R = RING, ROTATABLE FLANGE RETAINING 39T = RING, OVERPRESSURE 39E = RING, CENTERING W/ O-RING & OVERPRESSURE RING ASSEMBLY 39P = RING, CAPTURE 39F = RING, CENTERING W/ O-RING & CAPTURE RING ASSEMBLY 39L = RING, REDUCING CENTERING W/ O-RING ASSEMBLY</p> <hr/> <p>70 = HARDWARE, BOLTS & WASHERS 70B = HARDWARE, BOLTS, NUTS & WASHERS 70C = HARDWARE, 12-PT BOLTS & WASHERS 70D = HARDWARE, 12-PT BOLTS, NUTS & WASHERS 70P = HARDWARE, PLATE NUTS 70Q = HARDWARE, PLATE NUTS & BOLTS 70R = HARDWARE, PLATE NUTS, BOLTS & WASHERS 70S = HARDWARE, PLATE NUTS & 12-PT BOLTS 70T = HARDWARE, PLATE NUTS, 12-PT BOLTS & WASHERS 72R = O-RING 72G = GASKET</p>	<p>FLANGE TYPE¹ N = NW / KF K = ISO-K F = ISO-F (BOLTED) C = CF</p> <p>CENTERING RING TYPE² N = NW / KF S = ISO-K/ISO-F</p>	<p>NW / KF³ 1A = NW10 (1.18", 30mm O.D.) 1B = NW16 (1.18", 30mm O.D.) 1C = NW25 (1.58", 40mm O.D.) 1D = NW40 (2.16", 55mm O.D.) 1E = NW50 (2.95", 75mm O.D.) 1F = NW20 (1.58", 40mm O.D.) 1G = NW32 (2.16", 55mm O.D.)</p> <p>ISO-K / ISO-F 2A = ISO63 (3.74", 95mm O.D.) 2B = ISO80 (4.33", 110mm O.D.) 2C = ISO100 (5.12", 130mm O.D.) 2D = ISO160 (7.09", 180mm O.D.) 2E = ISO200 (9.45", 240mm O.D.) 2F = ISO250 (11.42", 290mm O.D.) 2G = ISO320 (14.75", 370mm O.D.) 2H = ISO400 (17.72", 450mm O.D.) 2J = ISO500 (21.65", 550mm O.D.)</p> <p>CF 3A = 1.33" (1.33", 33.8mm O.D.) 3B = 2.12" (2.12", 53.8mm O.D.) 3C = 2.75" (2.73", 69.3mm O.D.) 3D = 3.38" (3.36", 85.3mm O.D.) 3E = 4.50" (4.47", 113.5mm O.D.) 3F = 4.62" (4.61", 117.1mm O.D.) 3G = 6.00" (5.97", 151.6mm O.D.) 3H = 6.75" (6.73", 170.9mm O.D.) 3J = 8.00" (7.97", 202.4mm O.D.) 3K = 10.00" (9.97", 253.2mm O.D.) 3L = 12.00" (11.97", 304.0mm O.D.) 3M = 13.25" (13.25", 336.6mm O.D.) 3N = 14.00" (14.00", 355.6mm O.D.) 3P = 14.50" (14.50", 368.3mm O.D.) 3Q = 16.50" (16.50", 419.1mm O.D.)</p> <p>ISO-K CLAW CLAMP 4A = ISO63 - ISO100 4B = ISO160 - ISO250 4C = ISO320 - ISO500 4D = ISO63 - ISO250</p>		<p>CLAMP THREAD / MATERIAL⁴ CA = INCH, ALUMINUM CB = METRIC, ALUMINUM CC = INCH, 316 SS, ZINC PLATED NUT CD = METRIC, 316 SS, ZINC PLATED NUT CE = INCH, 304 SS</p> <p>GASKET MATERIAL G1 = OFHC COPPER G2 = SILVER PLATED OFHC COPPER G3 = PTFE</p>
FOR THE FOLLOWING CONFIGURATIONS SELECT ONE FROM EACH OPTION:					
		<p>RINGS & O-RING MATERIAL</p> <p>OPTION 1 - CENTERING RINGS X = NO CENTERING RING 1 = CENTERING RING, ALUMINUM 2 = CENTERING RING, 304 SS 3 = CENTERING RING, 316L SS 4 = CENTERING RING, 316L SS, EP 5 = CENTERING RING, 316 SS 6 = CENTERING RING, 316 SS, EP</p>	<p>OPTION 2 - O-RINGS X = NO O-RING A = NBR (BUNA) B = EPDM C = FKM (VITON) D = SILICONE E = KALREZ 6375 F = KALREZ 8900 G = KALREZ 9100 H = KALREZ 9500 J = KALREZ 8575 K = KALREZ 4079</p>	<p>OPTION 3 - RINGS (OUTER) X = NO RING A = SPACER, ALUMINUM D = OVERPRESSURE, ALUMINUM E = OVERPRESSURE, 304 SS F = OVERPRESSURE, 316 SS G = CAPTURE, ALUMINUM H = CAPTURE, 304 SS J = CAPTURE, 316 SS K = RETAINING, 304 SS</p>	<p>OPTION 4 - O-RING COLOR BLANK = BLACK B = BROWN G = GREEN</p>
		<p>OPTION 1 - PLATE NUT X = NO PLATE NUT P = PLATE NUT, 304 SS</p>	<p>OPTION 2 - MAT'L and/or THREAD X = NO BOLTS AND WASHERS S = INCH (PLATE NUT) M = METRIC (PLATE NUT) T = INCH, 10-8SS (BOLTS) U = INCH, 10-8SS, SILVER-PLATED (BOLTS) V = METRIC, 10-8SS (BOLTS) W = METRIC, 10-8SS, SILVER-PLATED (BOLTS)</p>	<p>OPTION 3 - BOLT LENGTH (SEE CATALOG FOR LENGTHS) X = NO BOLT A = STANDARD LENGTH A B = STANDARD LENGTH B C = STANDARD LENGTH C</p>	

Part Number Examples:

Double Claw Clamp: V0-13D-K2B-CA
 Plastic Dust Cap: V0-16D-K2D-PA
 Centering Ring w/ Viton O-ring: V0-39C-K2E-2CX
 Centering Ring w/ Viton O-ring & Aluminum Capture Ring Assembly: V0-39F-N1D-2CG
 Centering Ring: V0-39-K2F4-1XX
 Spacer Ring: V0-39S-K2C-XXA
 Rotatable Flange Retaining Ring: V0-39R-F2A-XXJ
 Reducing Centering Ring w/ O-ring: V0-39L-N1AXN1B-4CX
 Hardware, Plate Nuts: V0-70P-C3B-PSX
 Hardware, Bolts, Nuts & Washers: V0-70B-C3F-XTA
 Hardware, Plate Nuts, Bolts & Washers: V0-70R-C3H-PTA
 Copper Gasket V0-72G-N1C-G1
 Viton O-Ring: V0-72O-K2C-XXC

NOTES:

- NW/KF USE ISO FLANGE TYPE FOR FLANGE SIZE ISO 80 & ABOVE.
- NW/KF CENTERING RINGS ISO 80 & ABOVE USE THE "S" TYPE CODE DESIGNATOR IN P/N.
- NW/KF USE ISO CENTERING RING SIZE CODES FOR FLANGE SIZE ISO 80 & ABOVE.
- CHOOSE THE FOLLOWING MATERIAL FOR ISO CLAW CLAMP SIZES:
4A, 4B & 4C: ALUMINUM, 4C & 4D: STAINLESS STEEL
- NOT ALL POSSIBLE PART NUMBER CONFIGURATION ARE AVAILABLE.
PLEASE CONTACT VALEX FOR AVAILABILITY.

 www.valex.com		
TITLE VACUUM FITTINGS & HOSE ITEM NUMBER SCHEME		
SPECIFICATION SP-7200	SHEET 3 OF 4	REV O

VACUUM BELLOWS & FLEXIBLE HOSE PART NUMBER MATRIX

XX MATERIAL / FINISH ¹	- XXX CONFIGURATION CODE ²	- X TYPE CODE	XX SIZE CODE	X	X TYPE CODE	XX SIZE CODE	- XXX ATTRIBUTE CODE																																												
<p>STANDARD FINISH SS</p> <p>VA = 304 VD = 304L VC = 316L VQ = 316LN VT = V22[®] ALLOY (UNS N06022)* VW = ALLOY 276 (UNS N10276)</p> <p>MECHANICAL POLISHED SS</p> <p>VE = 304 VH = 304L VG = 316L VU = V22[®] ALLOY (UNS N06022)* VY = ALLOY 276 (UNS N10276)</p> <p>ELECTROPOLISHED SS</p> <p>VK = 304 EP VN = 304L EP VM = 316L EP VV = V22[®] ALLOY (UNS N06022)* VZ = ALLOY 276 (UNS N10276)</p>	<p>42B = BELLOWS, FORMED, 316L³ 42E = BELLOWS, EDGE WELDED 42H = HOSE, FORMED 42R = HOSE, BRAIDED FLEXIBLE 42T = BELLOWS, FORMED, 321³</p>	<p>CONNECTION TYPE</p> <p>W = WELD (BUTTWELD/SOCKET) T = COMPRESSION FITTING V = FACE SEAL, MALE U = FACE SEAL, FEMALE</p> <p>FLANGE TYPE</p> <p>N = NW / KF K = ISO-K F = ISO-F (BOLTED) C = CF</p>	<p>TUBE / PIPE / FITTING</p> <table border="0" style="width: 100%;"> <tr> <th style="text-align: left;">TUBE O.D.</th> <th style="text-align: left;">PIPE O.D.</th> </tr> <tr> <td>02 = 1/8"</td> <td>67 = 1/8 NPS / NPT</td> </tr> <tr> <td>04 = 1/4"</td> <td>68 = 1/4 NPS / NPT</td> </tr> <tr> <td>06 = 3/8"</td> <td>69 = 3/8 NPS / NPT</td> </tr> <tr> <td>08 = 1/2"</td> <td>70 = 1/2 NPS / NPT</td> </tr> <tr> <td>10 = 5/8"</td> <td>71 = 3/4 NPS / NPT</td> </tr> <tr> <td>12 = 3/4"</td> <td>72 = 1 NPS / NPT</td> </tr> <tr> <td>14 = 7/8"</td> <td>74 = 1-1/2 NPS / NPT</td> </tr> <tr> <td>16 = 1"</td> <td>84 = 12 NPS (12.75" O.D.)</td> </tr> <tr> <td>20 = 1-1/4"</td> <td></td> </tr> <tr> <td>24 = 1-1/2"</td> <td></td> </tr> <tr> <td>26 = 1-5/8"</td> <td></td> </tr> <tr> <td>28 = 1-3/4"</td> <td></td> </tr> <tr> <td>32 = 2"</td> <td></td> </tr> <tr> <td>40 = 2-1/2"</td> <td></td> </tr> <tr> <td>48 = 3"</td> <td></td> </tr> <tr> <td>64 = 4"</td> <td></td> </tr> <tr> <td>80 = 5"</td> <td></td> </tr> <tr> <td>96 = 6"</td> <td></td> </tr> <tr> <td>53 = 8"</td> <td></td> </tr> <tr> <td>55 = 10"</td> <td></td> </tr> <tr> <td>57 = 12"</td> <td></td> </tr> </table> <p>NW / KF FLANGE</p> <p>1A = NW10 (1.18", 30mm O.D.) 1B = NW16 (1.18", 30mm O.D.) 1C = NW25 (1.58", 40mm O.D.) 1D = NW40 (2.16", 55mm O.D.) 1E = NW50 (2.95", 75mm O.D.) 1F = NW20 (1.58", 40mm O.D.) 1G = NW32 (2.16", 55mm O.D.) 1H = NW80 (4.33", 110mm O.D.) 1J = NW100 (5.12", 130mm O.D.) 1K = NW160 (7.09", 180mm O.D.)</p> <p>ISO-K / ISO-F FLANGE</p> <p>2A = ISO63 (3.74", 95mm O.D.) 2B = ISO80 (4.33", 110mm O.D.) 2C = ISO100 (5.12", 130mm O.D.) 2D = ISO160 (7.09", 180mm O.D.) 2E = ISO200 (9.45", 240mm O.D.) 2F = ISO250 (11.42", 290mm O.D.) 2G = ISO320 (14.75", 370mm O.D.) 2H = ISO400 (17.72", 450mm O.D.) 2J = ISO500 (21.65", 50mm O.D.)</p> <p>CF FLANGE</p> <p>3A = 1.33" (1.33", 33.8mm O.D.) 3B = 2.12" (2.12", 53.8mm O.D.) 3C = 2.75" (2.73", 69.3mm O.D.) 3D = 3.38" (3.36", 85.3mm O.D.) 3E = 4.50" (4.47", 113.5mm O.D.) 3F = 4.62" (4.61", 117.1mm O.D.) 3G = 6.00" (5.97", 151.6mm O.D.) 3H = 6.75" (6.73", 170.9mm O.D.) 3J = 8.00" (7.97", 202.4mm O.D.) 3K = 10.00" (9.97", 253.2mm O.D.) 3L = 12.00" (11.97", 304.0mm O.D.) 3M = 13.25" (13.25", 336.6mm O.D.) 3N = 14.00" (14.00", 355.6mm O.D.) 3P = 14.50" (14.50", 368.3mm O.D.) 3Q = 16.50" (16.50", 419.1mm O.D.)</p>	TUBE O.D.	PIPE O.D.	02 = 1/8"	67 = 1/8 NPS / NPT	04 = 1/4"	68 = 1/4 NPS / NPT	06 = 3/8"	69 = 3/8 NPS / NPT	08 = 1/2"	70 = 1/2 NPS / NPT	10 = 5/8"	71 = 3/4 NPS / NPT	12 = 3/4"	72 = 1 NPS / NPT	14 = 7/8"	74 = 1-1/2 NPS / NPT	16 = 1"	84 = 12 NPS (12.75" O.D.)	20 = 1-1/4"		24 = 1-1/2"		26 = 1-5/8"		28 = 1-3/4"		32 = 2"		40 = 2-1/2"		48 = 3"		64 = 4"		80 = 5"		96 = 6"		53 = 8"		55 = 10"		57 = 12"			<p>SEE PREVIOUS COLUMN "TYPE CODE" FOR OPTIONS</p>	<p>SEE PREVIOUS COLUMN "SIZE CODE" FOR OPTIONS</p>	<p>BELLOWS LENGTH</p> <p>2.5 = 2.5" 3.0 = 3.0" 3.2 = 3.2" 3.5 = 3.5" 4.0 = 4.0" 4.2 = 4.2" 5.0 = 5.0" 5.2 = 5.2" 6.0 = 6.0" 7.0 = 7.0" 8.0 = 8.0" 8.2 = 8.2" 9.0 = 9.0"</p> <p>HOSE LENGTH</p> <p>10 = 10.0" 12 = 12.0" 18 = 18.0" 24 = 24.0" 30 = 30.0" 36 = 36.0" 42 = 42.0" 48 = 48.0" 54 = 54.0" 60 = 60.0" 72 = 72.0" 84 = 84.0" 96 = 96.0" 108 = 108.0" 120 = 120.0" 984 = 984.0"</p>
TUBE O.D.	PIPE O.D.																																																		
02 = 1/8"	67 = 1/8 NPS / NPT																																																		
04 = 1/4"	68 = 1/4 NPS / NPT																																																		
06 = 3/8"	69 = 3/8 NPS / NPT																																																		
08 = 1/2"	70 = 1/2 NPS / NPT																																																		
10 = 5/8"	71 = 3/4 NPS / NPT																																																		
12 = 3/4"	72 = 1 NPS / NPT																																																		
14 = 7/8"	74 = 1-1/2 NPS / NPT																																																		
16 = 1"	84 = 12 NPS (12.75" O.D.)																																																		
20 = 1-1/4"																																																			
24 = 1-1/2"																																																			
26 = 1-5/8"																																																			
28 = 1-3/4"																																																			
32 = 2"																																																			
40 = 2-1/2"																																																			
48 = 3"																																																			
64 = 4"																																																			
80 = 5"																																																			
96 = 6"																																																			
53 = 8"																																																			
55 = 10"																																																			
57 = 12"																																																			

NOTES:

1. FINISH OPTIONS ARE FOR END CONNECTIONS ONLY.
2. ALL BRAIDED HOSES ARE 304/304L.
3. BELLOWS BODY MATERIAL ONLY.
4. NOT ALL POSSIBLE PART NUMBER CONFIGURATION ARE AVAILABLE. PLEASE CONTACT VALEX FOR AVAILABILITY.

*MATERIAL: HAYNES HASTELLOY[®] C-22[®] IS AVAILABLE UPON REQUEST. HASTELLOY AND C-22 ARE REGISTERED TRADEMARKS OF HAYNES INTERNATIONAL INC.

Part Number Examples:

Bellows, 12" Length: VM-42B-N1CXN1C-4.0

Bellows, 12" Length: VM-42B-K2BXK2A-4.0

Hose, 12" Length: VM-42H-U04XU04-12

Hose, 120" Length: VM-42H-T04XT04-120



TITLE VACUUM FITTINGS & HOSE ITEM NUMBER SCHEME		
SPECIFICATION SP-7200	SHEET 4 OF 4	REV O