



GAS STICK PART NUMBER MATRIX	
G2 A - 04 04 C - 1 - 0 0	
<p><b>Gas Stick</b></p> <p>G = In-line Gas Stick</p> <p><b>G2 = Regulator &amp; Gauge w/ Mini Ball Valve</b></p> <p>G3 = Regulator &amp; Gauge Only</p> <hr/> <p><b>Regulator Size *</b></p> <p><b>A = 0.15 Cv</b></p> <p>B = 1.8 Cv</p> <hr/> <p><b>Inlet Size</b></p> <p><b>04 = 1/4"</b></p> <p>06 = 3/8"</p> <p>08 = 1/2"</p> <p>12 = 3/4"</p> <hr/> <p><b>Outlet Size</b></p> <p><b>04 = 1/4"</b></p> <p>06 = 3/8"</p> <p>08 = 1/2"</p> <p>12 = 3/4"</p>	<p><b>Outlet Filter Option (0.003 μM)</b></p> <p><b>0 = Not Required</b></p> <p>1 = TEM Filter (low flow)</p> <p>2 = TEM Filter (high flow)</p> <p>3 = Entegris Filter</p> <hr/> <p><b>Lockout and Mounting Bracket Options</b></p> <p><b>0 = Not Required</b></p> <p>1 = Mounting Bracket (Strut Channel Compatible)</p> <p>2 = Valve Lockout</p> <p>3 = Valve Lockout and Mounting Bracket</p> <hr/> <p><b>Gauge</b></p> <p><b>1 = -30inHg-160 psig</b></p> <hr/> <p><b>Connection Type</b></p> <p><b>C = Compression in, Compression out</b></p> <p>T=Tube in, Compression out</p>
<p>* 0.15 Cv size is typically used for 1/4" gas sticks, while 1.8 Cv is typically used on 3/8" &amp; 1/2" gas sticks.</p>	